

Radial Lead Fuses

Round - Fast Acting

multicompPRO



**RoHS
Compliant**

Electrical Characteristics

Rated Current	1.5 Inches	2.1 Inches	2.75 Inches		4 Inches		10 Inches
	Minimum	Maximum	Minimum	Maximum	Minimum	Maximum	Maximum
50mA to 5A	60 Minutes	30 Minutes	10ms	3 Seconds	3ms	300ms	20ms
6.3 A				5 Seconds			

Interrupting Ratings

35 A or 10 × rated current; whichever is greater at 250 V AC

Environmental Specifications

Operating Temperature	: -55°C to +125°C
Shock	: MIL-STD-202, method 213, condition 1 (saw tooth)
Vibration	: MIL-STD-202, method 201 (10 - 55 Hz × 3 axis / no load)
Salt Spray	: MIL-STD-202, method 101, test condition B (48 hours)
Minimum Insulation Resistance	: MIL-STD-202, method 302, test condition A (after opening) 10,000 Ω
Resistance to Solder Heat	: MIL-STD-202, method 210, test condition F (10 seconds at 260°C)
Thermal Shock	: MIL-STD-202, method 107, test condition B (-65°C to +125°C)
UL Approved	

Physical Specifications

Base and Cap Material	: Black Thermoplastic
Pin Material	: Tin-lead Plated Alloy

Specification Table

Part Number	Ampere Rating (In)	Voltage Rating (V)	Nominal Resistance Cold Ω	Maximum Voltage Drop (mV)	Nominal Melting I ² t A ² Seconds
MCMEF 800MA 250V	800mA	250	0.072	130	0.192
MCMEF 1A 250V	1A		0.052	120	0.3
MCMEF 1.25A 250V	1.25A		0.043		0.4687
MCMEF 1.6A 250V	1.6A		0.031	110	0.896
MCMEF 2A 250V	2A		0.026		1.2
MCMEF 2.5A 250V	2.5A		0.019	100	2.5
MCMEF 3.15A 250V	3.15A		0.014		3.969
MCMEF 4A 250V	4A		0.011		7.2
MCMEF 5A 250V	5A		0.0083	90	15
MCMEF 6.3A 250V	6.3A		0.0061	80	47.628

Newark.com/multicomp-pro
Farnell.com/multicomp-pro
sg.element14.com/b/multicomp-pro


multicompPRO

Radial Lead Fuses


Round - Fast Acting

multicompPRO

Time Current Characteristic Curve



Average Melting I^2t Curves



Newark.com/multicomp-pro
Farnell.com/multicomp-pro
sg.element14.com/b/multicomp-pro


multicompPRO

multicomp PRO

Diagram of a circular cross-section of a pipe. The diameter is labeled as 8.35. The pressure rating is labeled as 150 PSI.

(0.5 Minimum)

Lead Wire
(Copper Wire)



MCMEF

800mA

250V

Ampere Rating

Voltage Rating

Ampere Rating : 800mA, 1A, 1.25A, 1.6A, 2A, 2.5A, 3.15A, 4A, 5A and 6.3A

Dimensions : Millimetres

Important Notice : This data sheet and its contents (the "Information") belong to the members of the AVNET group of companies (the "Group") or are licensed to it. No licence is granted for the use of it other than for information purposes in connection with the products to which it relates. No licence of any intellectual property rights is granted. The Information is subject to change without notice and replaces all data sheets previously supplied. The Information supplied is believed to be accurate but the Group assumes no responsibility for its accuracy or completeness, any error in or omission from it or for any use made of it. Users of this data sheet should check for themselves the Information and the suitability of the products for their purpose and not make any assumptions based on information included or omitted. Liability for loss or damage resulting from any reliance on the Information or use of it (including liability resulting from negligence or where the Group was aware of the possibility of such loss or damage arising) is excluded. This will not operate to limit or restrict the Group's liability for death or personal injury resulting from its negligence. Multicomp Pro is the registered trademark of Premier Farnell Limited 2019.