



Safety Data Sheet according to (EC) No 1907/2006 as amended

Page 1 of 31

LOCTITE AA 3525 LC known as LOCTITE 3525 VIS/UV

SDS No. : 153626
V020.0

Revision: 21.10.2025

printing date: 22.10.2025

Replaces version from: 04.10.2024

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

LOCTITE AA 3525 LC known as LOCTITE 3525 VIS/UV
UFI: M17K-2XFD-120D-8HMJ

1.2. Relevant identified uses of the substance or mixture and uses advised against

Intended use:
UV curing anaerobic adhesive

1.3. Details of the supplier of the safety data sheet

Henkel Ltd
Adhesives
Wood Lane End
HP2 4RQ Hemel Hempstead

Great Britain

Phone: +44 (1442) 278000

SDSinfo.Adhesive@henkel.com

For Safety Data Sheet updates please visit our website www.mysds.henkel.com or www.henkel-adhesives.com.

1.4. Emergency telephone number

24 Hours Emergency Tel: +44 (0)1442 278497

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

Classification (CLP):

Skin irritation	Category 2
H315 Causes skin irritation.	
Serious eye damage	Category 1
H318 Causes serious eye damage.	
Skin sensitizer	Category 1
H317 May cause an allergic skin reaction.	
Toxic to reproduction	Category 1B
H360Fd May damage fertility. Suspected of damaging the unborn child.	
Specific target organ toxicity - single exposure	Category 3
H335 May cause respiratory irritation.	
Target organ: respiratory tract irritation	
Chronic hazards to the aquatic environment	Category 2
H411 Toxic to aquatic life with long lasting effects.	

2.2. Label elements

Label elements (CLP):

Hazard pictogram:



Contains

Isobornyl acrylate

2-Hydroxyethyl methacrylate

Acrylic acid

Hydroxypropyl methacrylate

Diphenyl-2,4,6-trimethylbenzoyl phosphine oxide

1-Hydroxycyclohexyl phenyl ketone

Signal word:

Danger

Hazard statement:

H315 Causes skin irritation.

H317 May cause an allergic skin reaction.

H318 Causes serious eye damage.

H335 May cause respiratory irritation.

H411 Toxic to aquatic life with long lasting effects.

H360Fd May damage fertility. Suspected of damaging the unborn child.

Supplemental information

Restricted to professional users.

**Precautionary statement:
Prevention**

P273 Avoid release to the environment.

P280 Wear protective gloves/protective clothing/eye protection/face protection.

P261 Avoid breathing vapors.

P201 Obtain special instructions before use.

**Precautionary statement:
Response**

P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

P302+P352 IF ON SKIN: Wash with plenty of soap and water.

P333+P313 If skin irritation or rash occurs: Get medical advice/attention.

P308+P313 IF exposed or concerned: Get medical advice/attention.

2.3. Other hazards

None if used properly.

Care should be taken during the cure of these products by UV radiation to avoid exposure of the skin and especially of the eyes to direct or reflected UV radiation as long term effects could be harmful.

Following substances are present in a concentration $\geq$ the concentration limit for depiction in Section 3 and fulfill the criteria for PBT/vPvB, or were identified as endocrine disruptor (ED):

This mixture does not contain any substances in a concentration $\geq$ the concentration limit for depiction in Section 3 that are assessed to be a PBT, vPvB or ED.

SECTION 3: Composition/information on ingredients

3.2. Mixtures

Declaration of the ingredients according to CLP (EC) No 1272/2008:

Hazardous components CAS No. EC No UK-REACH-Reg. No.	Concentration	Classification	Specific Conc. Limits, M-factors and ATEs	Add. Information
Isobornyl methacrylate 7534-94-3 231-403-1	10 - < 20 %	Skin Irrit. 2, H315 Eye Irrit. 2, H319 STOT SE 3, H335 Aquatic Chronic 3, H412	STOT SE 3; H335; C >= 10 %	
Isobornyl acrylate 5888-33-5 227-561-6	5 - < 10 %	Skin Sens. 1A, H317 Aquatic Acute 1, H400 Aquatic Chronic 1, H410	M acute = 1 M chronic = 1	
2-Hydroxyethyl methacrylate 868-77-9 212-782-2	5 - < 10 %	Skin Irrit. 2, H315 Skin Sens. 1, H317 Eye Irrit. 2, H319		
Acrylic acid 79-10-7 201-177-9	1 - < 5 %	Acute Tox. 4, Dermal, H312 Skin Corr. 1A, H314 Flam. Liq. 3, H226 Acute Tox. 4, Oral, H302 Acute Tox. 4, Inhalation, H332 Aquatic Acute 1, H400 Aquatic Chronic 2, H411 STOT SE 3, H335 Eye Dam. 1, H318	STOT SE 3; H335; C >= 1 % ===== M acute = 1 ===== dermal:ATE = 1.100 mg/kg inhalation:ATE = 11 mg/l; vapour	EU OEL
Hydroxypropyl methacrylate 27813-02-1 248-666-3	1 - < 5 %	Skin Sens. 1, H317 Eye Irrit. 2, H319		
1-Hydroxycyclohexyl phenyl ketone 947-19-3 213-426-9	1 - < 5 %	Aquatic Chronic 3, H412 Repr. 1B, H360F	oral:ATE = 2.500 mg/kg	
Diphenyl-2,4,6-trimethylbenzoyl phosphine oxide 75980-60-8 278-355-8	1 - < 5 %	Aquatic Chronic 2, H411 Skin Sens. 1B, H317 Repr. 1B, H360Fd		SVHC
[3-(2,3-Epoxypropoxy)propyl]trimethoxysilane 2530-83-8 219-784-2	1 - < 3 %	Aquatic Chronic 3, H412 Eye Dam. 1, H318		

If no ATE values are displayed, please refer to LD/LC50 values in Section 11.
For full text of the H - statements and other abbreviations see section 16 "Other information".

SECTION 4: First aid measures**4.1. Description of first aid measures**

Inhalation:

Move to fresh air. If symptoms persist, seek medical advice.

Consideration should be given to the possible effects of a faulty UV source (Stray radiation, ozone).

Skin contact:
Rinse with running water and soap.
Obtain medical attention if irritation persists.

Eye contact:
Rinse immediately with plenty of running water (for 10 minutes), seek medical attention from a specialist.

Ingestion:
Rinse mouth, drink 1-2 glasses of water, do not induce vomiting, consult a doctor.

4.2. Most important symptoms and effects, both acute and delayed

SKIN: Rash, Urticaria.

RESPIRATORY: Irritation, coughing, shortness of breath, chest tightness.

SKIN: Redness, inflammation.

After eye contact: Corrosive, may cause permanent damage to eyes (impairment of vision).

4.3. Indication of any immediate medical attention and special treatment needed

See section: Description of first aid measures

SECTION 5: Firefighting measures

5.1. Extinguishing media

Suitable extinguishing media:

Carbon dioxide, foam, powder

Extinguishing media which must not be used for safety reasons:

High pressure waterjet

5.2. Special hazards arising from the substance or mixture

In the event of a fire, carbon monoxide (CO), carbon dioxide (CO₂) and nitrogen oxides (NO_x) can be released.

5.3. Advice for firefighters

Wear self-contained breathing apparatus and full protective clothing, such as turn-out gear.

Additional information:

In case of fire, keep containers cool with water spray.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

Avoid contact with skin and eyes.

Ensure adequate ventilation.

Wear protective equipment.

Keep away from sources of ignition.

6.2. Environmental precautions

Do not empty into drains / surface water / ground water.

6.3. Methods and material for containment and cleaning up

For small spills wipe up with paper towel and place in container for disposal.

For large spills absorb onto inert absorbent material and place in sealed container for disposal.

Dispose of contaminated material as waste according to Section 13.

6.4. Reference to other sections

See advice in section 8

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Avoid skin and eye contact.

See advice in section 8

Ventilation will remove any ozone that may be produced by the ultra violet lamp

Hygiene measures:

Good industrial hygiene practices should be observed.

Wash hands before work breaks and after finishing work.

Do not eat, drink or smoke while working.

7.2. Conditions for safe storage, including any incompatibilities

Ensure good ventilation/extraction.

Keep container tightly sealed.

Refer to Technical Data Sheet.

7.3. Specific end use(s)

UV curing anaerobic adhesive

SECTION 8: Exposure controls/personal protection**8.1. Control parameters****Occupational Exposure Limits**

Valid for

Great Britain

Ingredient [Regulated substance]	ppm	mg/m ³	Value type	Short term exposure limit category / Remarks	Regulatory list
Acrylic acid 79-10-7 [ACRYLIC ACID (PROP-2-ENOIC ACID)]	10	29	Time Weighted Average (TWA):	Indicative	ECTLV
Acrylic acid 79-10-7 [ACRYLIC ACID (PROP-2-ENOIC ACID)]	20	59	Short Term Exposure Limit (STEL):	Indicative	ECTLV
Acrylic acid 79-10-7 [ACRYLIC ACID]	10	29	Time Weighted Average (TWA):		EH40 WEL
Acrylic acid 79-10-7 [Acrylic acid]	20	59	Short Term Exposure Limit (STEL):	1 minute	EH40 WEL

Occupational Exposure Limits

Valid for

Ireland

Ingredient [Regulated substance]	ppm	mg/m ³	Value type	Short term exposure limit category / Remarks	Regulatory list
Acrylic acid 79-10-7 [ACRYLIC ACID (PROP-2-ENOIC ACID)]	10	29	Time Weighted Average (TWA):	Indicative	ECTLV
Acrylic acid 79-10-7 [ACRYLIC ACID (PROP-2-ENOIC ACID)]	20	59	Short Term Exposure Limit (STEL):	Indicative	ECTLV
Acrylic acid 79-10-7 [ACRYLIC ACID]	10	29	Time Weighted Average (TWA):	Indicative OELV	IR_OEL
Acrylic acid 79-10-7 [Acrylic acid]	20	59	Short Term Exposure Limit (STEL):	1 minute Indicative OELV	IR_OEL

Predicted No-Effect Concentration (PNEC):

Name on list	Environmental Compartment	Exposure period	Value				Remarks
			mg/l	ppm	mg/kg	others	
Exo-1,7,7-trimethylbicyclo[2.2.1]hept-2-yl methacrylate 7534-94-3	aqua (freshwater)		4,66 µg/l				
Exo-1,7,7-trimethylbicyclo[2.2.1]hept-2-yl methacrylate 7534-94-3	Soil				0,118 mg/kg		
Exo-1,7,7-trimethylbicyclo[2.2.1]hept-2-yl methacrylate 7534-94-3	sewage treatment plant (STP)		2,45 mg/l				
Exo-1,7,7-trimethylbicyclo[2.2.1]hept-2-yl methacrylate 7534-94-3	sediment (freshwater)				0,604 mg/kg		
Exo-1,7,7-trimethylbicyclo[2.2.1]hept-2-yl methacrylate 7534-94-3	aqua (intermittent releases)		0,0179 mg/l				
Exo-1,7,7-trimethylbicyclo[2.2.1]hept-2-yl methacrylate 7534-94-3	aqua (marine water)		0,000466 mg/l				
Exo-1,7,7-trimethylbicyclo[2.2.1]hept-2-yl methacrylate 7534-94-3	sediment (marine water)				0,06 mg/kg		
Isobornyl acrylate 5888-33-5	aqua (freshwater)		0,001 mg/l				
Isobornyl acrylate 5888-33-5	aqua (intermittent releases)		0,007 mg/l				
Isobornyl acrylate 5888-33-5	aqua (marine water)		0,0001 mg/l				
Isobornyl acrylate 5888-33-5	sewage treatment plant (STP)		2 mg/l				
Isobornyl acrylate 5888-33-5	sediment (freshwater)				0,145 mg/kg		
Isobornyl acrylate 5888-33-5	sediment (marine water)				0,0145 mg/kg		
Isobornyl acrylate 5888-33-5	Soil				0,0285 mg/kg		
Isobornyl acrylate 5888-33-5	Predator						no potential for bioaccumulation
2-Hydroxyethyl methacrylate 868-77-9	aqua (freshwater)		0,482 mg/l				
2-Hydroxyethyl methacrylate 868-77-9	aqua (marine water)		0,482 mg/l				
2-Hydroxyethyl methacrylate 868-77-9	sewage treatment plant (STP)		10 mg/l				
2-Hydroxyethyl methacrylate 868-77-9	aqua (intermittent releases)		1 mg/l				
2-Hydroxyethyl methacrylate 868-77-9	sediment (freshwater)				3,79 mg/kg		
2-Hydroxyethyl methacrylate 868-77-9	sediment (marine water)				3,79 mg/kg		
2-Hydroxyethyl methacrylate 868-77-9	Soil				0,476 mg/kg		
2-Hydroxyethyl methacrylate 868-77-9	Predator						no potential for bioaccumulation
2-Hydroxyethyl methacrylate 868-77-9	Marine water - intermittent		1 mg/l				
Acrylic acid 79-10-7	aqua (freshwater)		0,003 mg/l				
Acrylic acid 79-10-7	aqua (marine water)		0,0003 mg/l				
Acrylic acid 79-10-7	sewage treatment plant (STP)		0,9 mg/l				
Acrylic acid	sediment				0,0236		

79-10-7	(freshwater)				mg/kg		
Acrylic acid	sediment				0,00236		
79-10-7	(marine water)				mg/kg		
Acrylic acid	Soil				1 mg/kg		
79-10-7							
Acrylic acid	oral				0,03 g/kg		
79-10-7							
Acrylic acid	Air						no hazard identified
79-10-7							
Methacrylic acid, monoester with propane-1,2-diol	aqua (freshwater)		0,904 mg/l				
27813-02-1							
Methacrylic acid, monoester with propane-1,2-diol	aqua (marine water)		0,0904 mg/l				
27813-02-1							
Methacrylic acid, monoester with propane-1,2-diol	sewage treatment plant (STP)		10 mg/l				
27813-02-1							
Methacrylic acid, monoester with propane-1,2-diol	aqua (intermittent releases)		0,972 mg/l				
27813-02-1							
Methacrylic acid, monoester with propane-1,2-diol	sediment (freshwater)				4,13 mg/kg		
27813-02-1							
Methacrylic acid, monoester with propane-1,2-diol	sediment (marine water)				0,413 mg/kg		
27813-02-1							
Methacrylic acid, monoester with propane-1,2-diol	Soil				0,295 mg/kg		
27813-02-1							
Methacrylic acid, monoester with propane-1,2-diol	Air						no hazard identified
27813-02-1							
Methacrylic acid, monoester with propane-1,2-diol	Predator						no potential for bioaccumulation
27813-02-1							
Hydroxycyclohexyl phenyl ketone	aqua (freshwater)		0,0144 mg/l				
947-19-3							
Hydroxycyclohexyl phenyl ketone	aqua (marine water)		0,00144 mg/l				
947-19-3							
Hydroxycyclohexyl phenyl ketone	aqua (intermittent releases)		0,144 mg/l				
947-19-3							
Hydroxycyclohexyl phenyl ketone	Sewage treatment plant		10 mg/l				
947-19-3							
Hydroxycyclohexyl phenyl ketone	sediment (freshwater)				0,186 mg/kg		
947-19-3							
Hydroxycyclohexyl phenyl ketone	sediment (marine water)				0,0186 mg/kg		
947-19-3							
Hydroxycyclohexyl phenyl ketone	Soil				0,0284 mg/kg		
947-19-3							
Hydroxycyclohexyl phenyl ketone	Predator						no potential for bioaccumulation
947-19-3							
Diphenyl(2,4,6-trimethylbenzoyl)phosphine oxide	aqua (freshwater)		0,0014 mg/l				
75980-60-8							
Diphenyl(2,4,6-trimethylbenzoyl)phosphine oxide	aqua (marine water)		0,00014 mg/l				
75980-60-8							
Diphenyl(2,4,6-trimethylbenzoyl)phosphine oxide	Freshwater - intermittent		0,014 mg/l				
75980-60-8							
Diphenyl(2,4,6-trimethylbenzoyl)phosphine oxide	Marine water - intermittent		0,0014 mg/l				
75980-60-8							
Diphenyl(2,4,6-trimethylbenzoyl)phosphine oxide	sediment (freshwater)				0,115 mg/kg		
75980-60-8							
Diphenyl(2,4,6-trimethylbenzoyl)phosphine oxide	sediment (marine water)				0,0115 mg/kg		
75980-60-8							
Diphenyl(2,4,6-trimethylbenzoyl)phosphine oxide	Soil				0,0222 mg/kg		

75980-60-8							
[3-(2,3-Epoxypropoxy)propyl]trimethoxysilane 2530-83-8	aqua (freshwater)		0,45 mg/l				
[3-(2,3-Epoxypropoxy)propyl]trimethoxysilane 2530-83-8	aqua (marine water)		0,045 mg/l				
[3-(2,3-Epoxypropoxy)propyl]trimethoxysilane 2530-83-8	sewage treatment plant (STP)		8,2 mg/l				
[3-(2,3-Epoxypropoxy)propyl]trimethoxysilane 2530-83-8	sediment (freshwater)				1,6 mg/kg		
[3-(2,3-Epoxypropoxy)propyl]trimethoxysilane 2530-83-8	sediment (marine water)				0,16 mg/kg		
[3-(2,3-Epoxypropoxy)propyl]trimethoxysilane 2530-83-8	Soil				0,063 mg/kg		
[3-(2,3-Epoxypropoxy)propyl]trimethoxysilane 2530-83-8	aqua (intermittent releases)		0,45 mg/l				

Derived No-Effect Level (DNEL):

Name on list	Application Area	Route of Exposure	Health Effect	Exposure Time	Value	Remarks
Exo-1,7,7-trimethylbicyclo[2.2.1]hept-2-yl methacrylate 7534-94-3	Workers	dermal	Long term exposure - systemic effects		1,04 mg/kg	
Exo-1,7,7-trimethylbicyclo[2.2.1]hept-2-yl methacrylate 7534-94-3	General population	dermal	Long term exposure - systemic effects		0,625 mg/kg	
Isobornyl acrylate 5888-33-5	Workers	inhalation	Long term exposure - systemic effects		4,9 mg/m3	no potential for bioaccumulation
Isobornyl acrylate 5888-33-5	Workers	dermal	Long term exposure - systemic effects		1,39 mg/kg	no potential for bioaccumulation
Isobornyl acrylate 5888-33-5	Workers	dermal	Long term exposure - local effects			no potential for bioaccumulation
Isobornyl acrylate 5888-33-5	Workers	dermal	Acute/short term exposure - local effects			no potential for bioaccumulation
Isobornyl acrylate 5888-33-5	General population	inhalation	Long term exposure - systemic effects		1,45 mg/m3	no potential for bioaccumulation
Isobornyl acrylate 5888-33-5	General population	dermal	Long term exposure - systemic effects		0,83 mg/kg	no potential for bioaccumulation
Isobornyl acrylate 5888-33-5	General population	dermal	Long term exposure - local effects			no potential for bioaccumulation
Isobornyl acrylate 5888-33-5	General population	dermal	Long term exposure - local effects			no potential for bioaccumulation
Isobornyl acrylate 5888-33-5	General population	oral	Long term exposure - systemic effects		0,83 mg/kg	no potential for bioaccumulation
2-Hydroxyethyl methacrylate 868-77-9	Workers	dermal	Long term exposure - systemic effects		1,3 mg/kg	no potential for bioaccumulation
2-Hydroxyethyl methacrylate 868-77-9	Workers	Inhalation	Long term exposure - systemic effects		4,9 mg/m3	no potential for bioaccumulation
2-Hydroxyethyl methacrylate 868-77-9	General population	dermal	Long term exposure - systemic effects		0,83 mg/kg	no potential for bioaccumulation
2-Hydroxyethyl methacrylate 868-77-9	General population	Inhalation	Long term exposure - systemic effects		2,9 mg/m3	no potential for bioaccumulation
2-Hydroxyethyl methacrylate 868-77-9	General population	oral	Long term exposure - systemic effects		0,83 mg/kg	no potential for bioaccumulation
Acrylic acid 79-10-7	Workers	inhalation	Long term exposure - local effects		30 mg/m3	no hazard identified
Acrylic acid 79-10-7	Workers	inhalation	Acute/short term exposure - local effects		30 mg/m3	no hazard identified
Acrylic acid 79-10-7	Workers	dermal	Acute/short term exposure - local effects		1 mg/cm2	no hazard identified
Acrylic acid 79-10-7	General population	dermal	Acute/short term exposure - local effects		1 mg/cm2	no hazard identified
Acrylic acid 79-10-7	General population	inhalation	Acute/short term exposure - local effects		3,6 mg/m3	no hazard identified
Acrylic acid 79-10-7	General population	inhalation	Long term exposure - local effects		3,6 mg/m3	no hazard identified
Methacrylic acid, monoester with propane-1,2-diol	Workers	dermal	Long term exposure -		4,2 mg/kg	no hazard identified

27813-02-1			systemic effects			
Methacrylic acid, monoester with propane-1,2-diol 27813-02-1	Workers	Inhalation	Long term exposure - systemic effects		14,7 mg/m3	no hazard identified
Methacrylic acid, monoester with propane-1,2-diol 27813-02-1	General population	dermal	Long term exposure - systemic effects		2,5 mg/kg	no hazard identified
Methacrylic acid, monoester with propane-1,2-diol 27813-02-1	General population	Inhalation	Long term exposure - systemic effects		8,8 mg/m3	no hazard identified
Methacrylic acid, monoester with propane-1,2-diol 27813-02-1	General population	oral	Long term exposure - systemic effects		2,5 mg/kg	no hazard identified
Hydroxycyclohexyl phenyl ketone 947-19-3	Workers	inhalation	Long term exposure - systemic effects		4,93 mg/m3	no potential for bioaccumulation
Hydroxycyclohexyl phenyl ketone 947-19-3	Workers	dermal	Long term exposure - systemic effects		1,4 mg/kg	no potential for bioaccumulation
Hydroxycyclohexyl phenyl ketone 947-19-3	General population	inhalation	Long term exposure - systemic effects		0,87 mg/m3	no potential for bioaccumulation
Hydroxycyclohexyl phenyl ketone 947-19-3	General population	dermal	Long term exposure - systemic effects		0,5 mg/kg	no potential for bioaccumulation
Hydroxycyclohexyl phenyl ketone 947-19-3	General population	oral	Long term exposure - systemic effects		0,5 mg/kg	no potential for bioaccumulation
Diphenyl(2,4,6-trimethylbenzoyl)phosphine oxide 75980-60-8	Workers	inhalation	Long term exposure - systemic effects		0,822 mg/m3	
Diphenyl(2,4,6-trimethylbenzoyl)phosphine oxide 75980-60-8	Workers	dermal	Long term exposure - systemic effects		0,233 mg/kg	
Diphenyl(2,4,6-trimethylbenzoyl)phosphine oxide 75980-60-8	General population	inhalation	Long term exposure - systemic effects		0,145 mg/m3	
Diphenyl(2,4,6-trimethylbenzoyl)phosphine oxide 75980-60-8	General population	dermal	Long term exposure - systemic effects		0,0833 mg/kg	
Diphenyl(2,4,6-trimethylbenzoyl)phosphine oxide 75980-60-8	General population	oral	Long term exposure - systemic effects		0,0833 mg/kg	
[3-(2,3-Epoxypropoxy)propyl]trimethoxysilane 2530-83-8	Workers	dermal	Long term exposure - systemic effects		10 mg/kg	
[3-(2,3-Epoxypropoxy)propyl]trimethoxysilane 2530-83-8	Workers	Inhalation	Long term exposure - systemic effects		70,5 mg/m3	
[3-(2,3-Epoxypropoxy)propyl]trimethoxysilane 2530-83-8	General population	inhalation	Long term exposure - systemic effects		17,4 mg/m3	
[3-(2,3-Epoxypropoxy)propyl]trimethoxysilane 2530-83-8	General population	dermal	Long term exposure - systemic effects		5 mg/kg	
[3-(2,3-Epoxypropoxy)propyl]trimethoxysilane 2530-83-8	General population	inhalation	Acute/short term exposure - systemic effects		26400 mg/m3	
[3-(2,3-Epoxypropoxy)propyl]trimethoxysilane 2530-83-8	General population	oral	Long term exposure - systemic effects		4 mg/kg	

Biological Exposure Indices:

None

8.2. Exposure controls:

Engineering controls:

UV lamp should be designed, installed and operated in such a way as to eliminate exposure of the skin and eyes to stray radiation

Ensure good ventilation/extraction.

Respiratory protection:

Ensure adequate ventilation.

An approved mask or respirator fitted with an organic vapour cartridge should be worn if the product is used in a poorly ventilated area

Filter type: A (EN 14387)

Hand protection:

Chemical-resistant protective gloves (EN 374).

Suitable materials for short-term contact or splashes (recommended: at least protection index 2, corresponding to > 30 minutes permeation time as per EN 374):

nitrile rubber (NBR; ≥ 0.4 mm thickness)

Suitable materials for longer, direct contact (recommended: protection index 6, corresponding to > 480 minutes permeation time as per EN 374):

nitrile rubber (NBR; ≥ 0.4 mm thickness)

This information is based on literature references and on information provided by glove manufacturers, or is derived by analogy with similar substances. Please note that in practice the working life of chemical-resistant protective gloves may be considerably shorter than the permeation time determined in accordance with EN 374 as a result of the many influencing factors (e.g. temperature). If signs of wear and tear are noticed then the gloves should be replaced.

Eye protection:

Safety glasses with sideshields or chemical safety goggles should be worn if there is a risk of splashing.

Protective eye equipment should conform to EN166.

Skin protection:

Wear suitable protective clothing.

Protective clothing should conform to EN 14605 for liquid splashes or to EN 13982 for dusts.

Advices to personal protection equipment:

The information provided on personal protective equipment is for guidance purposes only. A full risk assessment should be conducted prior to using this product to determine the appropriate personal protective equipment to suit local conditions.

Personal protective equipment should conform to the relevant EN standard.

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Delivery form	liquid
Colour	Clear
Odor	Acrylic
Physical state	liquid
Melting point	Not applicable, Product is a liquid
Solidification temperature	< 14 °C (< 57.2 °F)
Initial boiling point	> 140 °C (> 284 °F)
Flammability	The product is not flammable.
Explosive limits	Not applicable, The product is not flammable.
Flash point	71,1 °C (159.98 °F); Tagliabue closed cup
Auto-ignition temperature	396 °C (744.8 °F)
Decomposition temperature	> 105 °C (> 221 °F);
pH	8 - 9
(20 °C (68 °F); Conc.: 1 %; Solvent: Water)	
Viscosity (kinematic)	13.477 mm ² /s
(20 °C (68 °F);)	
Viscosity, dynamic	9.500 - 21.000 mPa.s LCT STM 10; Viscosity Brookfield
(Brookfield; Instrument: RVT; 25 °C (77 °F);	
speed of rotation: 20 min ⁻¹ ; Spindle No: 6)	
Solubility (qualitative)	Slightly soluble
(20 °C (68 °F); Solvent: Water)	
Partition coefficient: n-octanol/water	Not applicable
	Mixture
Vapour pressure	< 13,3 hPa
(20 °C (68 °F))	
Density	1,113 g/cm ³ None
(20 °C (68 °F))	
Relative vapour density:	> 1
(20 °C)	

Particle characteristics

Not applicable
Product is a liquid

9.2. Other information

Other information not applicable for this product

SECTION 10: Stability and reactivity

10.1. Reactivity

Reacts with strong oxidants.
Strong bases.
Acids.
Reducing agents.

10.2. Chemical stability

Stable under recommended storage conditions.

10.3. Possibility of hazardous reactions

See section reactivity

10.4. Conditions to avoid

Stable under normal conditions of storage and use.
Protect from direct sunlight.
Avoid contact with acids and oxidizing agents.

10.5. Incompatible materials

See section reactivity.

10.6. Hazardous decomposition products

carbon oxides.
Hydrocarbons
nitrogen oxides
Rapid polymerisation may generate excessive heat and pressure.

SECTION 11: Toxicological information**11.1 Information on hazard classes as defined in Regulation (EC) No 1272/2008****Acute oral toxicity:**

The mixture is classified based on calculation method referring to the classified substances present in the mixture.

Based on available data, the classification criteria are not met.

Hazardous substances CAS-No.	Value type	Value	Species	Method
Isobornyl methacrylate 7534-94-3	LD50	3.160 mg/kg	rat	not specified
Isobornyl acrylate 5888-33-5	LD50	4.350 mg/kg	rat	not specified
2-Hydroxyethyl methacrylate 868-77-9	LD50	5.564 mg/kg	rat	FDA Guideline
Acrylic acid 79-10-7	LD50	1.500 mg/kg	rat	equivalent or similar to OECD Guideline 401 (Acute Oral Toxicity)
Hydroxypropyl methacrylate 27813-02-1	LD50	> 2.000 mg/kg	rat	OECD Guideline 401 (Acute Oral Toxicity)
1-Hydroxycyclohexyl phenyl ketone 947-19-3	LD50	> 2.000 - < 5.000 mg/kg	rat	equivalent or similar to OECD Guideline 401 (Acute Oral Toxicity)
1-Hydroxycyclohexyl phenyl ketone 947-19-3	Acute toxicity estimate (ATE)	2.500 mg/kg		Expert judgement
Diphenyl-2,4,6- trimethylbenzoyl phosphine oxide 75980-60-8	LD50	> 5.000 mg/kg	rat	OECD Guideline 401 (Acute Oral Toxicity)
[3-(2,3- Epoxypropoxy)propyl]tri methoxysilane 2530-83-8	LD50	8.025 mg/kg	rat	equivalent or similar to OECD Guideline 401 (Acute Oral Toxicity)

Acute dermal toxicity:

The mixture is classified based on calculation method referring to the classified substances present in the mixture.

Based on available data, the classification criteria are not met.

Hazardous substances CAS-No.	Value type	Value	Species	Method
Isobornyl methacrylate 7534-94-3	LD50	> 3.000 mg/kg	rabbit	not specified
Isobornyl acrylate 5888-33-5	LD50	> 3.000 mg/kg	rabbit	not specified
2-Hydroxyethyl methacrylate 868-77-9	LD50	> 5.000 mg/kg	rabbit	not specified
Acrylic acid 79-10-7	Acute toxicity estimate (ATE)	1.100 mg/kg		Expert judgement
Hydroxypropyl methacrylate 27813-02-1	LD50	> 5.000 mg/kg	rabbit	not specified
1-Hydroxycyclohexyl phenyl ketone 947-19-3	LD50	> 5.000 mg/kg	rat	OECD Guideline 402 (Acute Dermal Toxicity)
Diphenyl-2,4,6- trimethylbenzoyl phosphine oxide 75980-60-8	LD50	> 2.000 mg/kg	rat	OECD Guideline 402 (Acute Dermal Toxicity)
[3-(2,3- Epoxypropoxy)propyl]tri methoxysilane 2530-83-8	LD50	4.250 mg/kg	rabbit	equivalent or similar to OECD Guideline 402 (Acute Dermal Toxicity)

Acute inhalative toxicity:

The mixture is classified based on calculation method referring to the classified substances present in the mixture.

Based on available data, the classification criteria are not met.

Hazardous substances CAS-No.	Value type	Value	Test atmosphere	Exposure time	Species	Method
Acrylic acid 79-10-7	LC0	5,1 mg/l	vapour	4 h	rat	equivalent or similar to OECD Guideline 403 (Acute Inhalation Toxicity)
Acrylic acid 79-10-7	Acute toxicity estimate (ATE)	11 mg/l	vapour			Expert judgement
1-Hydroxycyclohexyl phenyl ketone 947-19-3	LC50	> 1 mg/l	dust/mist	4 h	rat	equivalent or similar to OECD Guideline 403 (Acute Inhalation Toxicity)
[3-(2,3- Epoxypoxy)propyl]tri methoxysilane 2530-83-8	LC50	> 5,3 mg/l	dust/mist	4 h	rat	equivalent or similar to OECD Guideline 403 (Acute Inhalation Toxicity)

Skin corrosion/irritation:

The mixture is classified based on calculation method referring to the classified substances present in the mixture.

Hazardous substances CAS-No.	Result	Exposure time	Species	Method
Isobornyl methacrylate 7534-94-3	mildly irritating		rabbit	OECD Guideline 404 (Acute Dermal Irritation / Corrosion)
Isobornyl acrylate 5888-33-5	not irritating	24 h	rabbit	other guideline:
2-Hydroxyethyl methacrylate 868-77-9	slightly irritating	24 h	rabbit	Draize Test
Acrylic acid 79-10-7	Sub-Category 1A (corrosive)	3 min	rabbit	OECD Guideline 404 (Acute Dermal Irritation / Corrosion)
Hydroxypropyl methacrylate 27813-02-1	not irritating	24 h	rabbit	Draize Test
1-Hydroxycyclohexyl phenyl ketone 947-19-3	not irritating	24 h	rabbit	EPA OPP 81-5 (Acute Dermal Irritation)
Diphenyl-2,4,6- trimethylbenzoyl phosphine oxide 75980-60-8	not irritating	24 h	rabbit	not specified
[3-(2,3- Epoxypoxy)propyl]tri methoxysilane 2530-83-8	not irritating	24 h	rabbit	OECD Guideline 404 (Acute Dermal Irritation / Corrosion)

Serious eye damage/irritation:

The mixture is classified based on calculation method referring to the classified substances present in the mixture.

Hazardous substances CAS-No.	Result	Exposure time	Species	Method
Isobornyl methacrylate 7534-94-3	not irritating		rabbit	FDA Guideline
Isobornyl methacrylate 7534-94-3	slightly irritating		rabbit	Draize Test
Isobornyl acrylate 5888-33-5	not irritating		rabbit	other guideline:
2-Hydroxyethyl methacrylate 868-77-9	Category 2B (mildly irritating to eyes)		rabbit	Draize Test
Acrylic acid 79-10-7	Category 1 (irreversible effects on the eye)		rabbit	BASF Test
Hydroxypropyl methacrylate 27813-02-1	Category 2B (mildly irritating to eyes)		rabbit	Draize Test
1-Hydroxycyclohexyl phenyl ketone 947-19-3	not irritating		rabbit	OECD Guideline 405 (Acute Eye Irritation / Corrosion)
Diphenyl-2,4,6- trimethylbenzoyl phosphine oxide 75980-60-8	not irritating		rabbit	not specified
[3-(2,3- Epoxypropoxy)propyl]tri methoxysilane 2530-83-8	corrosive		rabbit	OECD Guideline 405 (Acute Eye Irritation / Corrosion)

Respiratory or skin sensitization:

The mixture is classified based on threshold limits referring to the classified substances present in the mixture.

Hazardous substances CAS-No.	Result	Test type	Species	Method
Isobornyl methacrylate 7534-94-3	not sensitising	Guinea pig maximisation test	guinea pig	OECD Guideline 406 (Skin Sensitisation)
Isobornyl acrylate 5888-33-5	sensitising	Mouse local lymphnode assay (LLNA)	mouse	OECD Guideline 429 (Skin Sensitisation: Local Lymph Node Assay)
2-Hydroxyethyl methacrylate 868-77-9	not sensitising	Buehler test	guinea pig	Buehler test
2-Hydroxyethyl methacrylate 868-77-9	sensitising	Guinea pig maximisation test	guinea pig	Magnusson and Kligman Method
Acrylic acid 79-10-7	not sensitising	Freund's complete adjuvant test	guinea pig	Klecak Method
Acrylic acid 79-10-7	not sensitising	Split adjuvant test	guinea pig	Maguire Method
Hydroxypropyl methacrylate 27813-02-1	not sensitising	Mouse local lymphnode assay (LLNA)	mouse	equivalent or similar to OECD Guideline 429 (Skin Sensitisation: Local Lymph Node Assay)
Hydroxypropyl methacrylate 27813-02-1	sensitising	Guinea pig maximisation test	guinea pig	not specified
1-Hydroxycyclohexyl phenyl ketone 947-19-3	not sensitising	Guinea pig maximisation test	guinea pig	OECD Guideline 406 (Skin Sensitisation)
Diphenyl-2,4,6- trimethylbenzoyl phosphine oxide 75980-60-8	sensitising	Mouse local lymphnode assay (LLNA)	mouse	OECD Guideline 429 (Skin Sensitisation: Local Lymph Node Assay)
[3-(2,3- Epoxypoxypropyl)tri methoxysilane 2530-83-8	not sensitising	Buehler test	guinea pig	OECD Guideline 406 (Skin Sensitisation)

Germ cell mutagenicity:

The mixture is classified based on threshold limits referring to the classified substances present in the mixture.

Based on available data, the classification criteria are not met.

Hazardous substances CAS-No.	Result	Type of study / Route of administration	Metabolic activation / Exposure time	Species	Method
Isobornyl methacrylate 7534-94-3	negative	bacterial reverse mutation assay (e.g Ames test)	with and without		OECD Guideline 471 (Bacterial Reverse Mutation Assay)
Isobornyl methacrylate 7534-94-3	negative		with and without		OECD Guideline 476 (In vitro Mammalian Cell Gene Mutation Test)
Isobornyl methacrylate 7534-94-3	negative	in vitro mammalian chromosome aberration test	with and without		OECD Guideline 473 (In vitro Mammalian Chromosome Aberration Test)
Isobornyl acrylate 5888-33-5	negative	bacterial reverse mutation assay (e.g Ames test)	with and without		OECD Guideline 471 (Bacterial Reverse Mutation Assay)
Isobornyl acrylate 5888-33-5	negative	mammalian cell gene mutation assay	with and without		OECD Guideline 476 (In vitro Mammalian Cell Gene Mutation Test)
Isobornyl acrylate 5888-33-5	negative	in vitro mammalian cell micronucleus test	with and without		OECD Guideline 487 (In vitro Mammalian Cell Micronucleus Test)
2-Hydroxyethyl methacrylate 868-77-9	negative	bacterial reverse mutation assay (e.g Ames test)	with and without		OECD Guideline 471 (Bacterial Reverse Mutation Assay)
2-Hydroxyethyl methacrylate 868-77-9	positive	in vitro mammalian chromosome aberration test	with and without		OECD Guideline 473 (In vitro Mammalian Chromosome Aberration Test)
2-Hydroxyethyl methacrylate 868-77-9	negative	mammalian cell gene mutation assay	with and without		OECD Guideline 476 (In vitro Mammalian Cell Gene Mutation Test)
Acrylic acid 79-10-7	negative	bacterial reverse mutation assay (e.g Ames test)	with and without		equivalent or similar to OECD Guideline 471 (Bacterial Reverse Mutation Assay)
Acrylic acid 79-10-7	negative	mammalian cell gene mutation assay	with and without		equivalent or similar to OECD Guideline 476 (In vitro Mammalian Cell Gene Mutation Test)
Acrylic acid 79-10-7	negative	DNA damage and repair assay, unscheduled DNA synthesis in mammalian cells in vitro	without		equivalent or similar to OECD Guideline 482 (Genetic Toxicology: DNA Damage and Repair, Unscheduled DNA Synthesis in Mammalian Cells)
Hydroxypropyl methacrylate 27813-02-1	negative	bacterial reverse mutation assay (e.g Ames test)	with and without		OECD Guideline 471 (Bacterial Reverse Mutation Assay)
Hydroxypropyl methacrylate 27813-02-1	positive	in vitro mammalian chromosome aberration test	with and without		Chromosome Aberration Test
Hydroxypropyl methacrylate 27813-02-1	negative	mammalian cell gene mutation assay	with and without		OECD Guideline 476 (In vitro Mammalian Cell Gene Mutation Test)
1-Hydroxycyclohexyl phenyl ketone 947-19-3	negative	bacterial reverse mutation assay (e.g Ames test)	with and without		OECD Guideline 471 (Bacterial Reverse Mutation Assay)
1-Hydroxycyclohexyl phenyl ketone 947-19-3	negative	mammalian cell gene mutation assay	with and without		OECD Guideline 476 (In vitro Mammalian Cell Gene Mutation Test)
Diphenyl-2,4,6- trimethylbenzoyl phosphine oxide 75980-60-8	negative	bacterial reverse mutation assay (e.g Ames test)	with and without		OECD Guideline 471 (Bacterial Reverse Mutation Assay)
Diphenyl-2,4,6- trimethylbenzoyl phosphine oxide 75980-60-8	negative	in vitro mammalian chromosome aberration test	with and without		OECD Guideline 473 (In vitro Mammalian Chromosome Aberration Test)

Diphenyl-2,4,6-trimethylbenzoyl phosphine oxide 75980-60-8	negative	mammalian cell gene mutation assay	with and without		OECD Guideline 476 (In vitro Mammalian Cell Gene Mutation Test)
[3-(2,3-Epoxypropoxy)propyl]tri methoxysilane 2530-83-8	A mutagenic potential can not be excluded.	mammalian cell gene mutation assay	with and without		OECD Guideline 476 (In vitro Mammalian Cell Gene Mutation Test)
2-Hydroxyethyl methacrylate 868-77-9	negative	oral: gavage		rat	OECD Guideline 474 (Mammalian Erythrocyte Micronucleus Test)
2-Hydroxyethyl methacrylate 868-77-9	negative	oral: gavage		Drosophila melanogaster	not specified
Acrylic acid 79-10-7	negative	oral: gavage		rat	equivalent or similar to OECD Guideline 475 (Mammalian Bone Marrow Chromosome Aberration Test)
Acrylic acid 79-10-7	negative	oral: gavage		mouse	not specified
Hydroxypropyl methacrylate 27813-02-1	negative	oral: gavage		mouse	OECD Guideline 474 (Mammalian Erythrocyte Micronucleus Test)
Hydroxypropyl methacrylate 27813-02-1	negative	oral: gavage		Drosophila melanogaster	not specified
1-Hydroxycyclohexyl phenyl ketone 947-19-3	negative	oral: gavage		hamster, Chinese	OECD Guideline 474 (Mammalian Erythrocyte Micronucleus Test)
[3-(2,3-Epoxypropoxy)propyl]tri methoxysilane 2530-83-8	A mutagenic potential can not be excluded.			mouse	OECD Guideline 474 (Mammalian Erythrocyte Micronucleus Test)

Carcinogenicity

The mixture is classified based on threshold limits referring to the classified substances present in the mixture.

Based on available data, the classification criteria are not met.

Hazardous components CAS-No.	Result	Route of application	Exposure time / Frequency of treatment	Species	Sex	Method
2-Hydroxyethyl methacrylate 868-77-9	not carcinogenic	inhalation	2 y 6 h/d, 5 d/w	rat	female	equivalent or similar OECD Guideline 451 (Carcinogenicity Studies)
2-Hydroxyethyl methacrylate 868-77-9	not carcinogenic	inhalation	2 y 6 h/d, 5 d/w	rat	male	equivalent or similar OECD Guideline 451 (Carcinogenicity Studies)
Acrylic acid 79-10-7	not carcinogenic	oral: drinking water	26 - 28 m continuously	rat	male/female	OECD Guideline 451 (Carcinogenicity Studies)
Acrylic acid 79-10-7	not carcinogenic	dermal	21 m 3 times/w	mouse	male/female	not specified
Hydroxypropyl methacrylate 27813-02-1	not carcinogenic	inhalation	2 y 6 h/d, 5 d/w	rat	male	equivalent or similar OECD Guideline 451 (Carcinogenicity Studies)
[3-(2,3-Epoxypropoxy)propyl]tri methoxysilane 2530-83-8	not carcinogenic	dermal	lifetime 3 applications/ week	mouse	male	not specified

Reproductive toxicity:

The mixture is classified based on threshold limits referring to the classified substances present in the mixture.

Hazardous substances CAS-No.	Result / Value	Test type	Route of application	Species	Method
Isobornyl methacrylate 7534-94-3	NOAEL P 25 mg/kg NOAEL F1 500 mg/kg		oral: gavage	rat	OECD Guideline 421 (Reproduction / Developmental Toxicity Screening Test)
Isobornyl acrylate 5888-33-5	NOAEL P 100 mg/kg NOAEL F1 100 mg/kg	screening	oral: gavage	rat	OECD Guideline 422 (Combined Repeated Dose Toxicity Study with the Reproduction / Developmental Toxicity Screening Test)
2-Hydroxyethyl methacrylate 868-77-9	NOAEL P $\geq$ 1.000 mg/kg NOAEL F1 $\geq$ 1.000 mg/kg	screening	oral: gavage	rat	equivalent or similar to OECD Guideline 422 (Combined Repeated Dose Toxicity Study)
Acrylic acid 79-10-7	NOAEL P 83 mg/kg NOAEL F1 250 mg/kg	one- generation study	oral: drinking water	rat	equivalent or similar to OECD Guideline 415 (One- Generation Reproduction Toxicity Study)
Acrylic acid 79-10-7	NOAEL P 240 mg/kg NOAEL F1 53 mg/kg NOAEL F2 53 mg/kg	two- generation study	oral: drinking water	rat	OECD Guideline 416 (Two- Generation Reproduction Toxicity Study)
Hydroxypropyl methacrylate 27813-02-1	NOAEL P 300 mg/kg NOAEL F1 1.000 mg/kg	screening	oral: gavage	rat	OECD Guideline 422 (Combined Repeated Dose Toxicity Study with the Reproduction / Developmental Toxicity Screening Test)
Hydroxypropyl methacrylate 27813-02-1	NOAEL P 400 mg/kg NOAEL F1 400 mg/kg	two- generation study	oral: gavage	rat	OECD Guideline 416 (Two- Generation Reproduction Toxicity Study)
1-Hydroxycyclohexyl phenyl ketone 947-19-3	NOAEL P 500 mg/kg	one- generation study	oral: gavage	rabbit	other guideline:
[3-(2,3- Epoxypropoxy)propyl]tri methoxysilane 2530-83-8	NOAEL P 1.000 mg/kg	One generation study	oral: gavage	rat	OECD Guideline 415 (One- Generation Reproduction Toxicity Study)

STOT-single exposure:

The mixture is classified based on threshold limits referring to the classified substances present in the mixture.

Hazardous substances CAS-No.	Assessment	Route of exposure	Target Organs	Remarks
Acrylic acid 79-10-7	May cause respiratory irritation.			

STOT-repeated exposure:

The mixture is classified based on threshold limits referring to the classified substances present in the mixture.

Based on available data, the classification criteria are not met.

Hazardous substances CAS-No.	Result / Value	Route of application	Exposure time / Frequency of treatment	Species	Method
Isobornyl acrylate 5888-33-5	NOAEL 100 mg/kg	oral: gavage	once daily	rat	OECD Guideline 422 (Combined Repeated Dose Toxicity Study with the Reproduction / Developmental Toxicity Screening Test)
2-Hydroxyethyl methacrylate 868-77-9	NOAEL 100 mg/kg	oral: gavage	49 d daily	rat	OECD Guideline 422 (Combined Repeated Dose Toxicity Study with the Reproduction / Developmental Toxicity Screening Test)
2-Hydroxyethyl methacrylate 868-77-9	NOAEL 0,352 mg/l	inhalation	90 d 6 h/d, 5 d/w	rat	OECD Guideline 413 (Subchronic Inhalation Toxicity: 90-Day)
Acrylic acid 79-10-7	NOAEL 40 mg/kg	oral: drinking water	12 m daily	rat	equivalent or similar to OECD Guideline 452 (Chronic Toxicity Studies)
Acrylic acid 79-10-7	NOAEL 0,015 mg/l	inhalation: vapour	90 d 6 h/d, 5 d/w	mouse	equivalent or similar to OECD Guideline 413 (Subchronic Inhalation Toxicity: 90-Day)
Hydroxypropyl methacrylate 27813-02-1	NOAEL 300 mg/kg	oral: gavage	49 d daily	rat	OECD Guideline 422 (Combined Repeated Dose Toxicity Study with the Reproduction / Developmental Toxicity Screening Test)
Hydroxypropyl methacrylate 27813-02-1	NOAEL 0,352 mg/l	inhalation	90 d 6 h/d, 5 d/w	rat	OECD Guideline 413 (Subchronic Inhalation Toxicity: 90-Day)
1-Hydroxycyclohexyl phenyl ketone 947-19-3	NOAEL 300 mg/kg	oral: gavage	91-92 d daily	rat	OECD Guideline 408 (Repeated Dose 90-Day Oral Toxicity in Rodents)
Diphenyl-2,4,6- trimethylbenzoyl phosphine oxide 75980-60-8	NOAEL 100 mg/kg	oral: gavage	3 m 5 d/w	rat	OECD Guideline 408 (Repeated Dose 90-Day Oral Toxicity in Rodents)
[3-(2,3- Epoxypropoxy)propyl]tri methoxysilane 2530-83-8	NOAEL 1.000 mg/kg	oral: gavage	28 d 5 d / week	rat	OECD Guideline 407 (Repeated Dose 28-Day Oral Toxicity in Rodents)
[3-(2,3- Epoxypropoxy)propyl]tri methoxysilane 2530-83-8	NOAEL 0,225 mg/l	inhalation: aerosol	14 d 6 h / d, 4/5 exposures/week	rat	equivalent or similar to OECD Guideline 412 (Repeated Dose Inhalation Toxicity: 28/14-Day)

Aspiration hazard:

No data available.

11.2 Information on other hazards

11.2.1 Endocrine disrupting properties

For the following ingredient(s) information on adverse health effects caused by endocrine disrupting properties is publicly available on the ECHA website:

Substances identified as ED according to EU REACH SVHC list: <https://echa.europa.eu/candidate-list-table>

Hazardous components	CAS No.	Link ECHA website
Diphenyl-2,4,6-trimethylbenzoyl phosphine oxide	75980-60-8	

SECTION 12: Ecological information**General ecological information:**

Do not empty into drains / surface water / ground water.

12.1. Toxicity**Toxicity (Fish):**

The mixture is classified based on calculation method referring to the classified substances present in the mixture.

The table below presents the data of the classified substances present in the mixture.

Hazardous substances CAS-No.	Value type	Value	Exposure time	Species	Method
Isobornyl methacrylate 7534-94-3	LC50	1,79 mg/l	96 h	Danio rerio	OECD Guideline 203 (Fish, Acute Toxicity Test)
Isobornyl acrylate 5888-33-5	LC50	0,704 mg/l	96 h	Danio rerio	OECD Guideline 203 (Fish, Acute Toxicity Test)
2-Hydroxyethyl methacrylate 868-77-9	LC50	> 100 mg/l	96 h	Oryzias latipes	OECD Guideline 203 (Fish, Acute Toxicity Test)
Acrylic acid 79-10-7	LC50	27 mg/l	96 h	Salmo gairdneri (new name: Oncorhynchus mykiss)	EPA OTS 797.1400 (Fish Acute Toxicity Test)
Acrylic acid 79-10-7	NOEC	>= 10,1 mg/l	45 d	Oryzias latipes	OECD Guideline 210 (fish early life stage toxicity test)
Hydroxypropyl methacrylate 27813-02-1	LC50	493 mg/l	48 h	Leuciscus idus melanotus	DIN 38412-15
1-Hydroxycyclohexyl phenyl ketone 947-19-3	LC50	24 mg/l	96 h	Danio rerio	EU Method C.1 (Acute Toxicity for Fish)
1-Hydroxycyclohexyl phenyl ketone 947-19-3	NOEC	10 mg/l	32 d	Pimephales promelas	OECD Guideline 210 (fish early life stage toxicity test)
Diphenyl-2,4,6-trimethylbenzoyl phosphine oxide 75980-60-8	LC50	1,4 mg/l	96 h	Cyprinus carpio	OECD Guideline 203 (Fish, Acute Toxicity Test)
[3-(2,3-Epoxypropoxy)propyl]trimethoxysilane 2530-83-8	LC50	55 mg/l	96 h	Cyprinus carpio	EU Method C.1 (Acute Toxicity for Fish)

Toxicity (aquatic invertebrates):

The mixture is classified based on calculation method referring to the classified substances present in the mixture.

The table below presents the data of the classified substances present in the mixture.

Hazardous substances CAS-No.	Value type	Value	Exposure time	Species	Method
Isobornyl methacrylate 7534-94-3	EC50	> 2,57 mg/l	48 h	Daphnia magna	OECD Guideline 202 (Daphnia sp. Acute Immobilisation Test)
Isobornyl acrylate 5888-33-5	EC50	1 mg/l	48 h	Daphnia magna	OECD Guideline 202 (Daphnia sp. Acute Immobilisation Test)
2-Hydroxyethyl methacrylate 868-77-9	EC50	380 mg/l	48 h	Daphnia magna	OECD Guideline 202 (Daphnia sp. Acute Immobilisation Test)
Acrylic acid 79-10-7	EC50	95 mg/l	48 h	Daphnia magna	EPA OTS 797.1300 (Aquatic Invertebrate Acute Toxicity Test, Freshwater Daphnids)
Hydroxypropyl methacrylate 27813-02-1	EC50	> 143 mg/l	48 h	Daphnia magna	OECD Guideline 202 (Daphnia sp. Acute Immobilisation Test)
1-Hydroxycyclohexyl phenyl ketone 947-19-3	EC50	53,9 mg/l	48 h	Daphnia magna	OECD Guideline 202 (Daphnia sp. Acute Immobilisation Test)

Diphenyl-2,4,6-trimethylbenzoyl phosphine oxide 75980-60-8	EC50	3,53 mg/l	48 h	Daphnia magna	OECD Guideline 202 (Daphnia sp. Acute Immobilisation Test)
[3-(2,3-Epoxypropoxy)propyl]trimethoxysilane 2530-83-8	EC50	324 mg/l	48 h	Simocephalus vetulus	OECD Guideline 202 (Daphnia sp. Acute Immobilisation Test)

Chronic toxicity (aquatic invertebrates):

The mixture is classified based on calculation method referring to the classified substances present in the mixture.

The table below presents the data of the classified substances present in the mixture.

Hazardous substances CAS-No.	Value type	Value	Exposure time	Species	Method
Isobornyl methacrylate 7534-94-3	NOEC	0,233 mg/l	21 d	Daphnia magna	OECD 211 (Daphnia magna, Reproduction Test)
Isobornyl acrylate 5888-33-5	NOEC	0,092 mg/l	21 d	Daphnia magna	OECD 211 (Daphnia magna, Reproduction Test)
2-Hydroxyethyl methacrylate 868-77-9	NOEC	24,1 mg/l	21 d	Daphnia magna	OECD 211 (Daphnia magna, Reproduction Test)
Acrylic acid 79-10-7	NOEC	19 mg/l	21 d	Daphnia magna	EPA OTS 797.1330 (Daphnid Chronic Toxicity Test)
Hydroxypropyl methacrylate 27813-02-1	NOEC	45,2 mg/l	21 d	Daphnia magna	OECD 211 (Daphnia magna, Reproduction Test)
1-Hydroxycyclohexyl phenyl ketone 947-19-3	NOEC	0,3 mg/l	21 d	Daphnia magna	OECD 211 (Daphnia magna, Reproduction Test)
[3-(2,3-Epoxypropoxy)propyl]trimethoxysilane 2530-83-8	NOEC	100 mg/l	21 d	Daphnia magna	OECD 211 (Daphnia magna, Reproduction Test)

Toxicity (Algae):

The mixture is classified based on calculation method referring to the classified substances present in the mixture.

The table below presents the data of the classified substances present in the mixture.

Hazardous substances CAS-No.	Value type	Value	Exposure time	Species	Method
Isobornyl methacrylate 7534-94-3	EC50	2,66 mg/l	96 h	Pseudokirchneriella subcapitata	OECD Guideline 201 (Alga, Growth Inhibition Test)
Isobornyl methacrylate 7534-94-3	NOEC	0,254 mg/l	96 h	Pseudokirchneriella subcapitata	OECD Guideline 201 (Alga, Growth Inhibition Test)
Isobornyl acrylate 5888-33-5	NOEC	0,405 mg/l	72 h	Pseudokirchneriella subcapitata	OECD Guideline 201 (Alga, Growth Inhibition Test)
Isobornyl acrylate 5888-33-5	EC50	1,98 mg/l	72 h	Pseudokirchneriella subcapitata	OECD Guideline 201 (Alga, Growth Inhibition Test)
2-Hydroxyethyl methacrylate 868-77-9	EC50	836 mg/l	72 h	Selenastrum capricornutum (new name: Pseudokirchneriella subcapitata)	OECD Guideline 201 (Alga, Growth Inhibition Test)
2-Hydroxyethyl methacrylate 868-77-9	NOEC	400 mg/l	72 h	Selenastrum capricornutum (new name: Pseudokirchneriella subcapitata)	OECD Guideline 201 (Alga, Growth Inhibition Test)
Acrylic acid 79-10-7	EC10	0,03 mg/l	72 h	Scenedesmus subspicatus (new name: Desmodesmus subspicatus)	EU Method C.3 (Algal Inhibition test)
Acrylic acid 79-10-7	EC50	0,13 mg/l	72 h	Scenedesmus subspicatus (new name: Desmodesmus subspicatus)	EU Method C.3 (Algal Inhibition test)
Hydroxypropyl methacrylate 27813-02-1	EC50	> 97,2 mg/l	72 h	Pseudokirchneriella subcapitata	OECD Guideline 201 (Alga, Growth Inhibition Test)
Hydroxypropyl methacrylate 27813-02-1	NOEC	> 97,2 mg/l	72 h	Pseudokirchneriella subcapitata	OECD Guideline 201 (Alga, Growth Inhibition Test)
1-Hydroxycyclohexyl phenyl ketone 947-19-3	EC50	14,4 mg/l	72 h	Desmodesmus subspicatus	OECD Guideline 201 (Alga, Growth Inhibition Test)
1-Hydroxycyclohexyl phenyl ketone 947-19-3	EC10	2,51 mg/l	72 h	Desmodesmus subspicatus	OECD Guideline 201 (Alga, Growth Inhibition Test)
Diphenyl-2,4,6- trimethylbenzoyl phosphine oxide 75980-60-8	EC50	> 2,01 mg/l	72 h	Pseudokirchneriella subcapitata	OECD Guideline 201 (Alga, Growth Inhibition Test)
Diphenyl-2,4,6- trimethylbenzoyl phosphine oxide 75980-60-8	EC10	1,56 mg/l	72 h	Pseudokirchneriella subcapitata	OECD Guideline 201 (Alga, Growth Inhibition Test)
[3-(2,3- Epoxypropoxy)propyl]trimeth oxysilane 2530-83-8	EC50	350 mg/l	96 h	Pseudokirchneriella subcapitata	OECD Guideline 201 (Alga, Growth Inhibition Test)
[3-(2,3- Epoxypropoxy)propyl]trimeth oxysilane 2530-83-8	NOEC	130 mg/l	96 h	Pseudokirchneriella subcapitata	OECD Guideline 201 (Alga, Growth Inhibition Test)

Toxicity (microorganisms):

The mixture is classified based on calculation method referring to the classified substances present in the mixture.

The table below presents the data of the classified substances present in the mixture.

Hazardous substances CAS-No.	Value type	Value	Exposure time	Species	Method
2-Hydroxyethyl methacrylate 868-77-9	EC0	> 3.000 mg/l	16 h	Pseudomonas fluorescens	other guideline:
Acrylic acid 79-10-7	EC20	900 mg/l	30 min	activated sludge, domestic	ISO 8192 (Test for Inhibition of Oxygen Consumption by Activated Sludge)
Hydroxypropyl methacrylate 27813-02-1	EC10	1.140 mg/l	16 h		not specified
1-Hydroxycyclohexyl phenyl ketone 947-19-3	EC10	> 100 mg/l	3 h	activated sludge	EU Method C.11 (Biodegradation: Activated Sludge Respiration Inhibition Test)

Diphenyl-2,4,6-trimethylbenzoyl phosphine oxide 75980-60-8	EC50	> 1.000 mg/l	30 min		OECD Guideline 209 (Activated Sludge, Respiration Inhibition Test)
[3-(2,3-Epoxypropoxy)propyl]trimethoxysilane 2530-83-8	EC50	> 100 mg/l	3 h	activated sludge of a predominantly domestic sewage	OECD Guideline 209 (Activated Sludge, Respiration Inhibition Test)

12.2. Persistence and degradability

The table below presents the data of the classified substances present in the mixture.

Hazardous substances CAS-No.	Result	Test type	Degradability	Exposure time	Method
Isobornyl methacrylate 7534-94-3	readily biodegradable	aerobic	70 %	28 d	OECD Guideline 310 (Ready Biodegradability/CO ₂ in Sealed Vessels (Headspace Test))
Isobornyl acrylate 5888-33-5	inherently biodegradable	aerobic	73,9 %	60 d	OECD Guideline 301 F (Ready Biodegradability: Manometric Respirometry Test)
Isobornyl acrylate 5888-33-5	not readily biodegradable.	aerobic	57 %	28 d	OECD Guideline 310 (Ready Biodegradability/CO ₂ in Sealed Vessels (Headspace Test))
2-Hydroxyethyl methacrylate 868-77-9	readily biodegradable	aerobic	92 - 100 %	14 d	OECD Guideline 301 C (Ready Biodegradability: Modified MITI Test (I))
Acrylic acid 79-10-7	inherently biodegradable	aerobic	100 %	28 d	OECD Guideline 302 B (Inherent biodegradability: Zahn-Wellens/EMPA Test)
Acrylic acid 79-10-7	readily biodegradable	aerobic	81 %	28 d	OECD Guideline 301 D (Ready Biodegradability: Closed Bottle Test)
Hydroxypropyl methacrylate 27813-02-1	readily biodegradable	aerobic	94,2 %	28 d	OECD Guideline 301 E (Ready biodegradability: Modified OECD Screening Test)
1-Hydroxycyclohexyl phenyl ketone 947-19-3	readily biodegradable	aerobic	73 %	28 d	EU Method C.4-C (Determination of the "Ready" Biodegradability/Carbon Dioxide Evolution Test)
Diphenyl-2,4,6-trimethylbenzoyl phosphine oxide 75980-60-8	not readily biodegradable.	aerobic	0 - 10 %	28 d	OECD Guideline 301 F (Ready Biodegradability: Manometric Respirometry Test)
[3-(2,3-Epoxypropoxy)propyl]trimethoxysilane 2530-83-8	not readily biodegradable.	aerobic	37 %	28 d	EU Method C.4-A (Determination of the "Ready" Biodegradability/Dissolved Organic Carbon (DOC) Die-Away Test)

12.3. Bioaccumulative potential

The table below presents the data of the classified substances present in the mixture.

Hazardous substances CAS-No.	Bioconcentration factor (BCF)	Exposure time	Temperature	Species	Method
Isobornyl methacrylate 7534-94-3	37	56 day	24 °C	Danio rerio	OECD Guideline 305 E (Bioaccumulation: Flow-through Fish Test)
Isobornyl acrylate 5888-33-5	37	56 h	24 °C	Danio rerio	OECD Guideline 305 (Bioconcentration: Flow-through Fish Test)
Acrylic acid 79-10-7	3,16				QSAR (Quantitative Structure Activity Relationship)
1-Hydroxycyclohexyl phenyl ketone 947-19-3	> 3,5 - 12	56 d		Cyprinus carpio	OECD Guideline 305 C (Bioaccumulation: Test for the Degree of Bioconcentration in Fish)

12.4. Mobility in soil

The table below presents the data of the classified substances present in the mixture.

Hazardous substances CAS-No.	LogPow	Temperature	Method
Isobornyl methacrylate 7534-94-3	5,09		OECD Guideline 117 (Partition Coefficient (n-octanol / water), HPLC Method)
Isobornyl acrylate 5888-33-5	4,52		OECD Guideline 117 (Partition Coefficient (n-octanol / water), HPLC Method)
2-Hydroxyethyl methacrylate 868-77-9	0,42	25 °C	OECD Guideline 107 (Partition Coefficient (n-octanol / water), Shake Flask Method)
Acrylic acid 79-10-7	0,46	25 °C	OECD Guideline 107 (Partition Coefficient (n-octanol / water), Shake Flask Method)
Hydroxypropyl methacrylate 27813-02-1	0,97	20 °C	not specified
1-Hydroxycyclohexyl phenyl ketone 947-19-3	2,81	25 °C	OECD Guideline 107 (Partition Coefficient (n-octanol / water), Shake Flask Method)
Diphenyl-2,4,6- trimethylbenzoyl phosphine oxide 75980-60-8	3,1	23 °C	OECD Guideline 117 (Partition Coefficient (n-octanol / water), HPLC Method)
[3-(2,3- Epoxypropoxy)propyl]trimeth oxysilane 2530-83-8	0,5	20 °C	QSAR (Quantitative Structure Activity Relationship)

12.5. Results of PBT and vPvB assessment

This mixture does not contain any substances that are assessed to be a PBT or vPvB.

12.6. Endocrine disrupting properties

For the following ingredient(s) information on adverse health effects caused by endocrine disrupting properties is publicly available on the ECHA website:

Substances identified as ED according to EU REACH SVHC list: <https://echa.europa.eu/candidate-list-table>

Hazardous components	CAS No.	Link ECHA website
Diphenyl-2,4,6- trimethylbenzoyl phosphine oxide	75980-60-8	

12.7. Other adverse effects

No data available.

SECTION 13: Disposal considerations

13.1. Waste treatment methods

Product disposal:

Dispose of in accordance with local and national regulations.

Do not empty into drains / surface water / ground water.

Disposal of uncleaned packages:

After use, tubes, cartons and bottles containing residual product should be disposed of as chemically contaminated waste in an authorised legal land fill site or incinerated.

Waste code

08 04 09* waste adhesives and sealants containing organic solvents and other dangerous substances

The valid EWC waste code numbers are source-related. The manufacturer is therefore unable to specify EWC waste codes for the articles or products used in the various sectors. The EWC codes listed are intended as a recommendation for users. We will be happy to advise you.

SECTION 14: Transport information

14.1. UN number or ID number

ADR	3082
RID	3082
ADN	3082
IMDG	3082
IATA	3082

14.2. UN proper shipping name

ADR	ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. (Isobornyl acrylate)
RID	ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. (Isobornyl acrylate)
ADN	ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. (Isobornyl acrylate)
IMDG	ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. (Isobornyl acrylate)
IATA	Environmentally hazardous substance, liquid, n.o.s. (Isobornyl acrylate)

14.3. Transport hazard class(es)

ADR	9
RID	9
ADN	9
IMDG	9
IATA	9

14.4. Packing group

ADR	III
RID	III
ADN	III
IMDG	III
IATA	III

14.5. Environmental hazards

ADR	Environmentally Hazardous
RID	Environmentally Hazardous
ADN	Environmentally Hazardous
IMDG	Marine Pollutant
IATA	Environmentally Hazardous

14.6. Special precautions for user

ADR	not applicable
-----	----------------

	Tunnelcode:
RID	not applicable
ADN	not applicable
IMDG	not applicable
IATA	not applicable

The transport classifications in this section apply generally to packed and bulk goods alike. For containers with a net volume of no more than 5 L for liquid substances or a net mass of no more than 5 kg for solid substances per individual or inner package, the exemptions SP 375 (ADR), A197 (IATA), 2.10.2.7 (IMDG), NZ 4.3(10) may be applied, which can result in a deviation from the transport classification for packed goods.

14.7. Maritime transport in bulk according to IMO instruments

not applicable

SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

Ozone Depleting Substance (ODS) (Regulation (EC) No 2024/590):	Not applicable
Prior Informed Consent (PIC) (Regulation (EU) No 649/2012):	Not applicable
Persistent organic pollutants (Regulation (EU) 2019/1021):	Not applicable

VOC content (2010/75/EC)	< 5,00 %
-----------------------------	----------

15.2. Chemical safety assessment

A chemical safety assessment has been carried out.

SECTION 16: Other information

The labelling of the product is indicated in Section 2. The full text of all abbreviations indicated by codes in this safety data sheet are as follows:

H226 Flammable liquid and vapour.
H302 Harmful if swallowed.
H312 Harmful in contact with skin.
H314 Causes severe skin burns and eye damage.
H315 Causes skin irritation.
H317 May cause an allergic skin reaction.
H318 Causes serious eye damage.
H319 Causes serious eye irritation.
H332 Harmful if inhaled.
H335 May cause respiratory irritation.
H360F May damage fertility.
H360Fd May damage fertility. Suspected of damaging the unborn child.
H400 Very toxic to aquatic life.
H410 Very toxic to aquatic life with long lasting effects.
H411 Toxic to aquatic life with long lasting effects.
H412 Harmful to aquatic life with long lasting effects.

Abbreviations and acronyms:

ADG(-Code): Australian Dangerous Goods (Code)
ADN: European Agreement concerning the International Carriage of Dangerous Goods by Inland Waterways
ADR : European Agreement concerning the International Carriage of Dangerous Goods by Road
ASTM: American Society for Testing and Materials
ATE: acute toxicity estimate
AS: Australian Standard
AwSV: Ordinance on Installations for the Handling of Substances Hazardous to Water
CAS: Chemical Abstract Service
CLP: Regulation (EC) No 1272/2008
CMR: cancerogenic, mutagenic or reprotoxic
DIN: German Institute for Standardization
ECx: Effective concentration (x% effective level)
ECHA: European Chemicals Agency
EC-Nummer: Substance number in the EU-inventories EINECS/ELINCS
ECTLV: European community threshold limit value
ED: Substance identified as having endocrine disrupting properties
EINECS: European Inventory of Existing Commercial Chemical Substances
ELINCS: European List of Notified Chemical Substances
EN : European Standard
ENCS: Japanese chemical inventory
EPA: US Environmental Protection Agency
EU: European Union
EU EXPLD1: Substance listed in Annex I, Reg (EC) No. 2019/1148
EU EXPLD2: Substance listed in Annex II, Reg (EC) No. 2019/1148
EWC: European Waste Catalogue
GHS: Globally Harmonised System for Classification and Labelling of Chemicals
GLP: Good Laboratory Practice
HSNO: Hazardous Substances and New Organisms
IARC: International Agency for Research of Cancer
IATA: International Air Transport Association
IBC-Code: International Code for the Construction and Equipment of Ships carrying Dangerous Chemicals in Bulk
IC50: half maximal inhibitory concentration
ICAO: International Civil Aviation Organization
IMDG-Code: International Maritime Code for Dangerous Goods
IMO: International Maritime Organization
ISO: International Standardization Organisation
LC50: Median lethal concentration
LD50: Median lethal dose
MARPOL: International Convention for the Prevention of Marine Pollution from Ships
n.o.s.: not otherwise specified
NO(A)EC: No (adverse) effect concentration
NO(A)EL: No (adverse) effect level

NZS: New Zealand Standard
OECD: Organisation for Economic Co-operation and Development
OEL: Occupational Exposure Limit
OPPT: US EPA Office of Pollution Prevention and Toxics
OPPTS: US EPA Office of Prevention, Pesticides and Toxic Substances
PBT: Persistent, bioaccumulative, toxic
(Q)SAR: (Quantitative) structure–activity relationship
REACH: Regulation (EC) No. 1907/2006
RID: Regulations concerning the International Transport of Dangerous Goods by Rail
SADT: Self Accelerating Decomposition Temperature
SDS: Safety Data Sheet
STOT: Specific Target Organ Toxicity
STOT SE: Specific Target Organ Toxicity - single exposure
STOT RE: Specific Target Organ Toxicity - repeated exposure
SUSMP: Standard for the Uniform Scheduling of Medicines and Poisons
SVHC: Substance of very high concern (REACH Candidate List)
TRGS: German Technical Rules for hazardous substances
UN: United Nations
VOC: Volatile Organic Compound
814.018 VOC Reg CH: Swiss Ordinance 814.018 on the Incentive Tax on Volatile Organic Compounds
vPvB: Very persistent, very bioaccumulative
VwVwS: Administrative Regulation on Substances Hazardous to Waters
WGK: Water hazard class

Further information:

This Safety Data Sheet has been produced for sales from Henkel to parties purchasing from Henkel, is based on Regulation (EC) No 1907/2006 and provides information in accordance with applicable regulations of the European Union only. In that respect, no statement, warranty or representation of any kind is given as to compliance with any statutory laws or regulations of any other jurisdiction or territory other than the European Union. When exporting to territories other than the European Union, please consult with the respective Safety Data Sheet of the concerned territory to ensure compliance or liaise with Henkel's Product Safety and Regulatory Affairs Department (SDSinfo.Adhesive@henkel.com) prior to export to other territories than the European Union.

This information is based on our current level of knowledge and relates to the product in the state in which it is delivered. It is intended to describe our products from the point of view of safety requirements and is not intended to guarantee any particular properties.

Dear Customer,

Henkel is committed to creating a sustainable future by promoting opportunities along the entire value chain. If you would like to contribute by switching from a paper to the electronic version of SDS, please contact the local Customer Service representative. We recommend to use a non-personal email address (e.g. SDS@your_company.com).

Relevant changes in this safety data sheet are indicated by vertical lines at the left margin in the body of this document. Corresponding text is displayed in a different color on shadowed fields.