

**RoHS
Compliant**




Specifications

Current Rating	: 1.5A AC,DC
Voltage Rating	: 125V AC,DC
Contact Resistance	: 20mΩ Max.
Insulation Resistance	: 500MΩ Min.
Withstanding Voltage	: 1000V AC/minute
Temperature Range	: -40°C to +85°C

Material and Finish

Insulator	: PC (UL94V-2)
Insulator Colour	: Clean
Contact	: Copper Alloy
Plating	: Contact area Gold Plated, Other area Cold Flash

Diagram



Part Number	"A"
7001-6P4C	5.23mm
7001-6P6C	7.22mm

Part Number Table

Description	Part Number
Modular Connector, RJ11 Plug, 1 x 1 (Port), 6P4C, Cable Mount	7001-6P4C
Modular Connector, RJ12 Plug, 1 x 1 (Port), 6P6C, Cable Mount	7001-6P6C

Dimensions : Millimetres

Important Notice : This data sheet and its contents (the "Information") belong to the members of the AVNET group of companies (the "Group") or are licensed to it. No licence is granted for the use of it other than for information purposes in connection with the products to which it relates. No licence of any intellectual property rights is granted. The Information is subject to change without notice and replaces all data sheets previously supplied. The Information supplied is believed to be accurate but the Group assumes no responsibility for its accuracy or completeness, any error in or omission from it or for any use made of it. Users of this data sheet should check for themselves the Information and the suitability of the products for their purpose and not make any assumptions based on information included or omitted. Liability for loss or damage resulting from any reliance on the Information or use of it (including liability resulting from negligence or where the Group was aware of the possibility of such loss or damage arising) is excluded. This will not operate to limit or restrict the Group's liability for death or personal injury resulting from its negligence. Multicomp Pro is the registered trademark of Premier Farnell Limited 2019.

Newark.com/multicomp-pro
Farnell.com/multicomp-pro
sg.element14.com/b/multicomp-pro

multicomp^{PRO}