

Safety data sheet according to UK REACH

Page 1/11

Printing date 26.06.2025

Version number 10.00 (replaces version 9.01)

Revision: 26.06.2025

* SECTION 1: Identification of the substance/mixture and of the company/ undertaking

· 1.1 Product identifier

· Trade name: 419D

- **Other Means of Identification:** Acrylic Conformal Coating
- **Related Part Number:** 419D-Liquid, 419D-55ML, 419D-1L, 419D-4L, 419D-20L, 419D-200ML
- **UFI:** 57A0-30SD-P00Y-4RT3

· 1.2 Relevant identified uses of the substance or mixture and uses advised against

- **Application of the substance / the mixture** Conformal Coating
- **Uses advised against** Not available

· 1.3 Details of the supplier of the safety data sheet

· **Manufacturer/Supplier:**

MG Chemicals Ltd. (Head Office)
1210 Corporate Drive
Burlington, Ontario L7L 5R6
CANADA
+(1) 905-331-1396
info@mgchemicals.com

MG Chemicals
Heame House, 23 Bliston Street
Sedgely Dudley DY3 1JA.
United Kingdom
+(44) 1663 362888

MG Chemicalst Ltd.
18-20, Msida Road,
Gzira, GZR 1401
MALTA

- **Further information obtainable from:** sds@mgchemicals.com

· 1.4 Emergency telephone number:

3E (Access code: 335388)
+(44) 20 3514787
+(1) 760 476 3961
UK Toll free: +(0) 800 680 0425

Members of the public seeking specific information on poisons should contact:
In England and Wales: NHS 111 - dial 111
In Scotland: NHS 24 - dial 111

SECTION 2: Hazards identification

· 2.1 Classification of the substance or mixture

· **Classification according to Regulation (EC) No 1272/2008**

Flam. Liq. 2 H225 Highly flammable liquid and vapour.
Eye Irrit. 2 H319 Causes serious eye irritation.
STOT SE 3 H336 May cause drowsiness or dizziness.

· 2.2 Label elements

· **Labelling according to Regulation (EC) No 1272/2008**

The product is classified and labelled according to the GB CLP regulation.

(Contd. on page 2)

— GB —

Safety data sheet

according to UK REACH

Page 2/11

Printing date 26.06.2025

Version number 10.00 (replaces version 9.01)

Revision: 26.06.2025

Trade name: 419D

(Contd. of page 1)

Hazard pictograms



GHS02 GHS07

Signal word Danger

Hazard-determining components of labelling:

n-butyl acetate

Butan-2-one

Hazard statements

H225 Highly flammable liquid and vapour.

H319 Causes serious eye irritation.

H336 May cause drowsiness or dizziness.

Precautionary statements

P102 Keep out of reach of children.

P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.

P233 Keep container tightly closed.

P271 Use only outdoors or in a well-ventilated area.

P280 Wear protective gloves, protective clothing, and eye protection.

P405 Store locked up.

P501 Dispose of contents and container in accordance with local, regional, and national regulations.

Additional information:

EUH066 Repeated exposure may cause skin dryness or cracking.

2.3 Other hazards

Results of PBT and vPvB assessment

PBT: Not applicable.

vPvB: Not applicable.

Determination of endocrine-disrupting properties

78-93-3	Butan-2-one	List II
---------	-------------	---------

SECTION 3: Composition/information on ingredients

3.2 Mixtures

Description: Mixture of substances listed below with nonhazardous additions.

Dangerous components:

CAS: 123-86-4 EINECS: 204-658-1 Index number: 607-025-00-1	n-butyl acetate Flam. Liq. 3, H226; STOT SE 3, H336, EUH066	55%
CAS: 78-93-3 EINECS: 201-159-0 Index number: 606-002-00-3	Butan-2-one Flam. Liq. 2, H225; Eye Irrit. 2, H319; STOT SE 3, H336, EUH066	15%
CAS: 80-62-6 EINECS: 201-297-1 Index number: 607-035-00-6	methyl methacrylate Flam. Liq. 2, H225; Skin Irrit. 2, H315; Skin Sens. 1, H317; STOT SE 3, H335	<0.1%
CAS: 97-88-1 EINECS: 202-615-1 Index number: 607-033-00-5	n-butyl methacrylate Flam. Liq. 3, H226; Skin Irrit. 2, H315; Eye Irrit. 2, H319; Skin Sens. 1, H317; STOT SE 3, H335	<0.1%

(Contd. on page 3)

GB

Safety data sheet according to UK REACH

Page 3/11

Printing date 26.06.2025

Version number 10.00 (replaces version 9.01)

Revision: 26.06.2025

Trade name: 419D

(Contd. of page 2)

- **Additional information:** For the wording of the listed hazard phrases refer to section 16.

SECTION 4: First aid measures

· 4.1 Description of first aid measures

· **After inhalation:**

Remove person to fresh air and keep comfortable for breathing.

If feeling unwell: Call a POISON CENTRE or doctor.

· **After skin contact:**

Take off immediately all contaminated clothing.

Wash with plenty of soap and water.

· **After eye contact:**

Rinse cautiously with water for 20 minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

If eye irritation persists: Get medical advice or attention.

· **After swallowing:**

Rinse mouth.

Do NOT induce vomiting.

If symptoms persist consult doctor.

· 4.2 Most important symptoms and effects, both acute and delayed

No further relevant information available.

· 4.3 Indication of any immediate medical attention and special treatment needed

No further relevant information available.

SECTION 5: Firefighting measures

· 5.1 Extinguishing media

· **Suitable extinguishing agents:**

CO₂, powder or water spray. Fight larger fires with water spray or alcohol resistant foam.

· **For safety reasons unsuitable extinguishing agents:** Water with full jet

· 5.2 Special hazards arising from the substance or mixture

The liquid may float on water and ignite.

Vapors are heavier than air. Vapors may travel to sources of ignition near the ground. They can cause flash fire or ignite explosively.

Prevent fire-fighting wash from entering waterway or sewer system.

· **Hazardous combustion products:** Carbon Oxides (CO_x)

· 5.3 Advice for firefighters

· **Protective equipment:** No special measures required.

* SECTION 6: Accidental release measures

· 6.1 Personal precautions, protective equipment and emergency procedures

Wear protective equipment. Keep unprotected persons away.

Ensure adequate ventilation

Remove or keep away all sources of extreme heat or open flames.

(Contd. on page 4)

GB

Safety data sheet according to UK REACH

Page 4/11

Printing date 26.06.2025

Version number 10.00 (replaces version 9.01)

Revision: 26.06.2025

Trade name: 419D

(Contd. of page 3)

Avoid breathing mist, spray, or vapors.

- **6.2 Environmental precautions:** Do not allow to enter sewers/ surface or ground water.

- **6.3 Methods and material for containment and cleaning up:**

Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust).

Collect liquid in a sealable, chemical-resistant container.

Wash residue with a paper towel and place dirty towels in container.

Use soap and water to remove the last traces of residue.

- **6.4 Reference to other sections**

See Section 7 for information on safe handling.

See Section 8 for information on personal protection equipment.

See Section 13 for disposal information.

* SECTION 7: Handling and storage

- **7.1 Precautions for safe handling**

Wear protective gloves and eye protection.

Wash hands and exposed skin thoroughly after handling.

Take off contaminated clothing and wash it before reuse.

Avoid breathing mist, spray, or vapors.

- **Information about fire - and explosion protection:**

Keep ignition sources away - Do not smoke.

Protect against electrostatic charges.

- **7.2 Conditions for safe storage, including any incompatibilities**

- **Storage:**

- **Requirements to be met by storerooms and receptacles:** Store in a cool location.

- **Information about storage in one common storage facility:** Not required.

- **Further information about storage conditions:**

Store locked up.

Keep container tightly sealed.

Store in cool, dry conditions in well sealed receptacles.

- **Storage class:** 3

- **7.3 Specific end use(s)** No further relevant information available.

* SECTION 8: Exposure controls/personal protection

- **8.1 Control parameters**

· Ingredients with limit values that require monitoring at the workplace:	
123-86-4 n-butyl acetate	
WEL	Short-term value: 966 mg/m ³ , 200 ppm Long-term value: 724 mg/m ³ , 150 ppm
78-93-3 Butan-2-one	
WEL	Short-term value: 899 mg/m ³ , 300 ppm Long-term value: 600 mg/m ³ , 200 ppm Sk, BMGV

(Contd. on page 5)

— GB —

Safety data sheet

according to UK REACH

Page 5/11

Printing date 26.06.2025

Version number 10.00 (replaces version 9.01)

Revision: 26.06.2025

Trade name: 419D

(Contd. of page 4)

· Ingredients with biological limit values:	
78-93-3 Butan-2-one	
BMGV	70 µmol/L Medium: urine Sampling time: post shift Parameter: butan-2-one

· **Additional information:** The lists valid during the making were used as basis.

· 8.2 Exposure controls

- **Appropriate engineering controls** No further data; see section 7.
- **Individual protection measures, such as personal protective equipment**
 - **General protective and hygienic measures:**
Keep away from foodstuffs, beverages and feed.
Immediately remove all soiled and contaminated clothing
Wash hands before breaks and at the end of work.
Avoid contact with the eyes and skin.
 - **Respiratory protection:**
In case of brief exposure or low pollution use respiratory filter device. In case of intensive or longer exposure use self-contained respiratory protective device.
Advice should be sought from respiratory protection specialists.
 - **Hand protection**



Protective gloves: EN374

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation. Due to missing tests no recommendation to the glove material can be given for the product/ the preparation/ the chemical mixture. Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation

· **Material of gloves**

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

· **Penetration time of glove material**

The exact break through time has to be found out by the manufacturer of the protective gloves and has to be observed.

· **Eye/face protection**



Wear safety glasses: EN 166

SECTION 9: Physical and chemical properties

· 9.1 Information on basic physical and chemical properties

- **Physical state** Liquid
- **Form:** Low viscosity
- **Colour:** Clear

(Contd. on page 6)

— GB —

Safety data sheet

according to UK REACH

Page 6/11

Printing date 26.06.2025

Version number 10.00 (replaces version 9.01)

Revision: 26.06.2025

Trade name: 419D

(Contd. of page 5)

· Odour: · Odour threshold: · Melting point/freezing point: · Boiling point or initial boiling point and boiling range · Flammability · Lower and upper explosion limit · Lower: · Upper: · Flash point: · Auto-ignition temperature: · Decomposition temperature: · pH · Viscosity: · Kinematic viscosity at 20 °C · Dynamic: · Solubility · water: · Partition coefficient n-octanol/water (log value) · Vapour pressure: · Relative density at 20 °C: · Vapour density (air=1) at 20 °C: · Particle characteristics	- Fruit-like 0.007 ppm - Undetermined. ≥80 °C - Highly flammable. 1.6 Vol % 10.4 Vol % -9 °C (78-93-3 Butan-2-one) ≥400 °C - Not determined. - Not determined. - Not determined. 110 mm²/s - Not determined. - Not miscible or difficult to mix. - Not determined. - Not available 0.92 >2.5 - Not available
9.2 Other information	
· 9.2.1 Information with regard to physical hazard classes · Flammable liquids · 9.2.2 Other safety characteristics · Evaporation rate at 20 °C · Ignition temperature: · Explosive properties: · Solvent content: · Organic solvents: · VOC (EC)	- Highly flammable liquid and vapour. <1 - Product is not selfigniting. - Product is not explosive. However, formation of explosive air/vapour mixtures are possible. - Not available 70.00 %

SECTION 10: Stability and reactivity

- **10.1 Reactivity** No further relevant information available.
- **10.2 Chemical stability** Chemically stable at normal temperatures and pressures.
 - **Thermal decomposition / conditions to be avoided:**
No decomposition if used according to specifications.
- **10.3 Possibility of hazardous reactions** No dangerous reactions known.
- **10.4 Conditions to avoid** Avoid ignition sources, open flames, and incompatible substances.
- **10.5 Incompatible materials:**
Strong oxidizing agents

(Contd. on page 7)

— GB —

Safety data sheet

according to UK REACH

Page 7/11

Printing date 26.06.2025

Version number 10.00 (replaces version 9.01)

Revision: 26.06.2025

Trade name: 419D

Strong acids

(Contd. of page 6)

10.6 Hazardous decomposition products:

No dangerous decomposition products known.

Hazardous combustion products: see section 5.

SECTION 11: Toxicological information

11.1 Information on hazard classes as defined in Regulation (EC) No 1272/2008

Acute toxicity Based on available data, the classification criteria are not met.

LD/LC50 values relevant for classification:

123-86-4 n-butyl acetate

Oral	LD50	>10,768 mg/kg (rat)
Dermal	LD50	>17,600 mg/kg (rabbit)
Inhalative	LC50/4 h	>21 mg/L (rat)

78-93-3 Butan-2-one

Oral	LD50	2,737 mg/kg (rat)
Dermal	LD50	6,480 mg/kg (rabbit)
Inhalative	LC50/ 8 h	23,500 mg/m3 (rat)

80-62-6 methyl methacrylate

Oral	LD50	7,872 mg/kg (rat)
------	------	-------------------

97-88-1 n-butyl methacrylate

Oral	LD50	22,600 mg/kg (rat)
Dermal	LD50	11,300 mg/kg (rabbit)
Inhalative	LC50/4 h	4,910 mg/L (rat)

Primary irritant effect:

Skin corrosion/irritation Based on available data, the classification criteria are not met.

Serious eye damage/irritation Causes serious eye irritation.

Respiratory or skin sensitisation Based on available data, the classification criteria are not met.

Germ cell mutagenicity Based on available data, the classification criteria are not met.

Carcinogenicity Based on available data, the classification criteria are not met.

Reproductive toxicity Based on available data, the classification criteria are not met.

STOT-single exposure May cause drowsiness or dizziness.

STOT-repeated exposure Based on available data, the classification criteria are not met.

Aspiration hazard Based on available data, the classification criteria are not met.

Summary of Effects and Symptoms by Routes of Exposure

Eyes:

redness, serious irritation

pain

Skin:

redness, may cause mild irritation

dry skin

Inhalation:

dizziness or drowsiness

cough

headache

sore throat

nausea

(Contd. on page 8)

— GB —

Safety data sheet

according to UK REACH

Page 8/11

Printing date 26.06.2025

Version number 10.00 (replaces version 9.01)

Revision: 26.06.2025

Trade name: 419D

(Contd. of page 7)

· **Swallowed:**

vomiting
diarrhea
see inhalation symptoms

· **Subacute to chronic toxicity:**

· **Delayed and immediate effects as well as chronic effects from short and long-term exposure**
Prolonged or repeated exposure may defat skin and cause skin dryness and cracking, and local redness and discomfort.

· **11.2 Information on other hazards**

· Endocrine disrupting properties		
78-93-3	Butan-2-one	List II

SECTION 12: Ecological information

· **12.1 Toxicity**

· Aquatic toxicity:		
123-86-4 n-butyl acetate		
LC50 96h	18 mg/L (minnow)	

· **12.2 Persistence and degradability** No further relevant information available.

· **12.3 Bioaccumulative potential** No further relevant information available.

· **12.4 Mobility in soil** No further relevant information available.

· **12.5 Results of PBT and vPvB assessment**

- **PBT:** Not applicable.
- **vPvB:** Not applicable.

· **12.6 Endocrine disrupting properties** For information on endocrine disrupting properties see section 11.

· **12.7 Other adverse effects**

· **Additional ecological information:**

· **General notes:**

Water hazard class 3 (German Regulation) (Self-assessment): extremely hazardous for water
Do not allow product to reach ground water, water course or sewage system, even in small quantities.
Danger to drinking water if even extremely small quantities leak into the ground.

SECTION 13: Disposal considerations

· **13.1 Waste treatment methods**

· **Recommendation**

Must not be disposed together with household garbage. Do not allow product to reach sewage system.

· European waste catalogue	
HP3	Flammable
HP5	Specific Target Organ Toxicity (STOT)/Aspiration Toxicity

(Contd. on page 9)

— GB —

Safety data sheet

according to UK REACH

Page 9/11

Printing date 26.06.2025

Version number 10.00 (replaces version 9.01)

Revision: 26.06.2025

Trade name: 419D

(Contd. of page 8)

- **Uncleaned packaging:**
- **Recommendation:** Disposal must be made according to official regulations.

SECTION 14: Transport information

· 14.1 UN number or ID number	
· ADR, IMDG, IATA	UN1263
· 14.2 UN proper shipping name	
· ADR, IMDG	PAINT
· IATA	Paint
· 14.3 Transport hazard class(es)	
· ADR, IMDG, IATA	
	
· Class	3 Flammable liquids.
· Label	3
· 14.4 Packing group	
· ADR, IMDG, IATA	II
· 14.5 Environmental hazards:	Not applicable.
· 14.6 Special precautions for user	Not applicable.
· Hazard identification number (Kemler code):	33
· EMS Number:	F-E, <u>S</u> -E
· Stowage Category	B
· 14.7 Maritime transport in bulk according to IMO instruments	Not applicable.
· Transport/Additional information:	
	Limited Quantity
	419D-55ML, 419D-1L, 419D-4L
· ADR	
· Limited quantities (LQ)	5L
· Excepted quantities (EQ)	Code: E2 Maximum net quantity per inner packaging: 30 ml Maximum net quantity per outer packaging: 500 ml
· Transport category	2
· Tunnel restriction code	D/E

(Contd. on page 10)

— GB —

Safety data sheet

according to UK REACH

Page 10/11

Printing date 26.06.2025

Version number 10.00 (replaces version 9.01)

Revision: 26.06.2025

Trade name: 419D

(Contd. of page 9)

· IMDG · Limited quantities (LQ) · Excepted quantities (EQ)	5L Code: E2 Maximum net quantity per inner packaging: 30 ml Maximum net quantity per outer packaging: 500 ml
· UN "Model Regulation":	UN 1263 PAINT, 3, II

SECTION 15: Regulatory information

· 15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

· Poisons Act

· Regulated explosives precursors (Part 1)	None of the ingredients is listed.
· Regulated poisons (Part 2)	None of the ingredients is listed.
· Reportable explosives precursors (Part 3)	None of the ingredients is listed.
· Reportable poisons (Part 4)	None of the ingredients is listed.

· Directive 2012/18/EU

- **Named dangerous substances - ANNEX I** None of the ingredients is listed.
- **Seveso category P5c FLAMMABLE LIQUIDS**
- **Qualifying quantity (tonnes) for the application of lower-tier requirements** 5,000 t
- **Qualifying quantity (tonnes) for the application of upper-tier requirements** 50,000 t

· REGULATION (EC) No 1907/2006 ANNEX XVII Conditions of restriction: 3

· DIRECTIVE 2011/65/EU on the restriction of the use of certain hazardous substances in electrical and electronic equipment – Annex II		
None of the ingredients is listed.		
· Annex I - RESTRICTED EXPLOSIVES PRECURSORS (Upper limit value for the purpose of licensing under Article 5(3))		
None of the ingredients is listed.		
· Annex II - REPORTABLE EXPLOSIVES PRECURSORS		
None of the ingredients is listed.		
· Regulation (EC) No 273/2004 on drug precursors		
78-93-3	Butan-2-one	3
· Regulation (EC) No 111/2005 laying down rules for the monitoring of trade between the Community and third countries in drug precursors		
78-93-3	Butan-2-one	3

(Contd. on page 11)

Safety data sheet

according to UK REACH

Page 11/11

Printing date 26.06.2025

Version number 10.00 (replaces version 9.01)

Revision: 26.06.2025

Trade name: 419D

(Contd. of page 10)

- **15.2 Chemical safety assessment:** A Chemical Safety Assessment has not been carried out.

SECTION 16: Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

- **Relevant phrases**

- H225 Highly flammable liquid and vapour.
- H226 Flammable liquid and vapour.
- H315 Causes skin irritation.
- H317 May cause an allergic skin reaction.
- H319 Causes serious eye irritation.
- H335 May cause respiratory irritation.
- H336 May cause drowsiness or dizziness.
- EUH066 Repeated exposure may cause skin dryness or cracking.

- **Classification according to Regulation (EC) No 1272/2008**

Flammable liquids	On basis of test data
Serious eye damage/irritation Specific target organ toxicity (single exposure)	The classification of the mixture is generally based on the calculation method using substance data according to Regulation (EC) No 1272/2008.

- **Department issuing SDS:** Product safety department.

- **Contact:** sds@mgchemicals.com

- **Date of previous version:** 19.07.2024

- **Version number of previous version:** 9.01

- **Abbreviations and acronyms:**

ADR: Accord relatif au transport international des marchandises dangereuses par route (European Agreement Concerning the International Carriage of Dangerous Goods by Road)
 IMDG: International Maritime Code for Dangerous Goods
 IATA: International Air Transport Association
 GHS: Globally Harmonised System of Classification and Labelling of Chemicals
 EINECS: European Inventory of Existing Commercial Chemical Substances
 ELINCS: European List of Notified Chemical Substances
 CAS: Chemical Abstracts Service (division of the American Chemical Society)
 VOC: Volatile Organic Compounds (USA, EU)
 LC50: Lethal concentration, 50 percent
 LD50: Lethal dose, 50 percent
 PBT: Persistent, Bioaccumulative and Toxic
 vPvB: very Persistent and very Bioaccumulative
 Flam. Liq. 2: Flammable liquids – Category 2
 Flam. Liq. 3: Flammable liquids – Category 3
 Skin Irrit. 2: Skin corrosion/irritation – Category 2
 Eye Irrit. 2: Serious eye damage/eye irritation – Category 2
 Skin Sens. 1: Skin sensitisation – Category 1
 STOT SE 3: Specific target organ toxicity (single exposure) – Category 3

- *** Data compared to the previous version altered.**