

1. Information about the goods and manufacturer

Name of Goods

Dual Wall Flame-retardant Heat Shrink Tubing

Description of Goods

Heatshrink Tubing (Adhesive Lined) 4:1 Black 20.0mm 1.22m

Details of the supplier of the safety data sheet

Premier Farnell
150 Armley Road
Leeds LS12 2QQ
Tel. : +44 (0) 8701 202530

Emergency telephone number

+44 1865 407333

2. Chemical Properties

Ingredient	Chemical Formula	Function	Percentage	CAS No.
Polyolefin	(CH ₂ CH ₂) _n	Main Material	50%	9002-88-4
Magnesium hydroxide	Mg(OH) ₂	Flame Retardants	30%	1309-42-8
APP	-	Flame Retardants	10%	7723-14-0
Pigment	Pigment	Colorant	5%	83524-75-8
Ho-melt Adhesive	EVA	Sealant	5%	-

3. Hazard Information

Key Hazards	Toxicological Effects on Health: After the tubes are ignited, the flame will self-extinguish in a short time. A little fume will give off and have slight harm on the respiratory passage of the human body.
	Influence on Environment: It will cause air pollution when the tubes burn.
	Physical and Chemical Hazards: Normally it is in tubular shape, and shrink at 70-125°C, which perhaps is harmful.
	Special Hazards: When roasted or fumigated, the smoke given off will have impact on the eyes and respiratory system, and is harmful to the human body.
Main symptoms: Weep, sneeze, cough, etc. These symptoms can be relieved through breathing fresh air.	
Hazards generated when burning: The tubing will burn for a short period of time after being ignited.	

4. First-Aid Measures

First-aid measures for exposing in different occasions:

Inhalation	: During proper operation, there is no danger caused by inhalation.
Skin contact	: No damage to skin in normal contact. As skin is easily scratched by the tubes, the operators are suggested to put on gloves in operation.
Eye contact	: No harm.
Ingestion	: Not edible
Key harmful effects	: It will impact the respiratory System if you inhale smokes generated by the burning of the tubes.

Safety Data Sheet

multicompPRO

Protective measures for the rescuers

: Wear respiration protection equipment.

Suggestions to doctor

: Those who have suffered severe damage in respiratory system should keep on inhaling fresh air to relieve the symptom.

5. Fire-fighting Measures

Suitable fire-extinguishing agent short time.

: Dry Powder Extinguisher should be used in order to put out the fire in a

Special harms possibly incurred in fire-fighting

: Small amount of smoke will give off when the tubes burn, which will impact the respiratory system of human body.

Special fire-fighting procedures

: No

Special protective equipment for the fire-fighters

: Normal fire-extinguishing equipment.

6. Emergency measures for leakage

Attentions need to be paid by individuals

: No

Environmental notice

: No

Cleaning Method

: No

7. Operation and Storage

Operation

: The tubes will shrink when heated by oven or heat gun.

Storage

: Pack the tubes with cartons properly and place them at a shady place and at normal temperature.

8. Contact controls and personal protection

Contact controls

: Not harmful

Personal protective measures

: No

9. Physical and Chemical Properties

Outer Jacket

Properties		Test Method	Test result
Physical Properties	Tensile strength /MPa	ASTM D2671	≥10.4
	Elongation/%	ASTM D2671	≥300
	Tensile strength after aging/MPa	UL 224: 158°C×168hr	≥7.3
	Elongation after aging/%	UL 224: 158°C×168hr	≥200
	Heat Resistance	UL 224: 250°C×4hr	No viscosity No Cracking
	Cold blend	UL 224: -30°C×4hr	No Cracking
Electrical Properties	Dielectric Strength(KV/mm)	IEC243	≥20
	Volume resistance/Ω·cm	IEC93	≥1×10 ¹⁴

Newark.com/multicomp-pro

Farnell.com/multicomp-pro

sg.element14.com/b/multicomp-pro

multicompPRO

Safety Data Sheet

multicompPRO

Properties		Test Method	Test result
Chemical Properties	Anti Corrosion	UL 224 158°C×168hr	PASS
	Copper stability	UL 224 158°C×168hr	PASS
	Flammability	UL 224	VW-1
	Water Absorption %	ASTM-D570	≤0.5

Hot-melt adhesive

Property	Test Method	Test result
Water Absorption	ASTM D570	≤0.2
Softening Point	ASTM E28	95°C
Peel Strength (PE)	ASTM D1000	120N/25mm
Peel Strength (AL)	ASTM D1000	80N/25mm

10. Stability and Reactivity of the goods

Stability	: irresolvable
Hazardous effects under special conditions	: If exposed to fire, the products will burn in a short time and give off smoke.
Conditions to be avoided	: The products will shrink under high temperature.
Substance to be avoided	: Fire
Hazardous decomposition product	: Smoke

11. Toxicological Information

Acute Toxicity	: No
Partial Effect	: No
Allergic Reactions	: No
Slow toxicity or long-term toxicity	: No
Special Effects	: No

12. Ecological Information

Possible effects on environment	: The products are irresolvable naturally and are not harmful to animals, plants and aquatic life.
---------------------------------	--

13. Waste Disposal

Trash disposal treatment.	: It is suggested that the waste be collected to waste-collection station for treatment.
---------------------------	--

14. Transport Information

Regulations on international transportation	: No
U.N. code	: No
Regulations on Domestic transportation	: No
Special transportation method and notice	: Avoid distortion caused by extrusion and damage caused by edged tools.

Newark.com/multicomp-pro
Farnell.com/multicomp-pro
sg.element14.com/b/multicomp-pro

multicompPRO

15. Regulation Information

Applicable regulation : UL224

16: Other information

NA

Part Number

HS405

Important Notice : This data sheet and its contents (the "Information") belong to the members of the AVNET group of companies (the "Group") or are licensed to it. No licence is granted for the use of it other than for information purposes in connection with the products to which it relates. No licence of any intellectual property rights is granted. The Information is subject to change without notice and replaces all data sheets previously supplied. The Information supplied is believed to be accurate but the Group assumes no responsibility for its accuracy or completeness, any error in or omission from it or for any use made of it. Users of this data sheet should check for themselves the Information and the suitability of the products for their purpose and not make any assumptions based on information included or omitted. Liability for loss or damage resulting from any reliance on the Information or use of it (including liability resulting from negligence or where the Group was aware of the possibility of such loss or damage arising) is excluded. This will not operate to limit or restrict the Group's liability for death or personal injury resulting from its negligence. Multicomp Pro is the registered trademark of Premier Farnell Limited 2019.